

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 483)

Fir, 20" dia., for cor. to secs. 20, 21, 28, & 29, marked T20S S21 on NE, R8W S28 on SE, S29 on SW, S20 on NW face, with 4 notches on E & 2 on South edges; from which
 Fir, 36" dia., bears S.50°W., 32 lks. mkd: T20S R8W S29 BT
 Fir, 36" dia., bears N.45°W., 48 lks. mkd: T20S R8W S20 BT
 Fir, 36" dia., bears N.60°E., 62 lks. mkd: T20S R8W S21 BT
 Hemlock, 6" dia., bears S.30°E., 53 lks., mkd: T20S R8W S28 BT.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11355)

The cor. of secs. 20, 21, 28, & 29, monumented by a fir, 32" dia., marked with traces of scribe marks in the bark of NE & SE, S on SW & S20 on NW faces, with 4 notches on E & 2 on S side, from which the remaining orig. BTs:
 A fir, 34" dia., bears N.60°E., 67 lks., plainly blazed & healed. (Rec. 62 lks.)
 A dead fir, 50" dia. bears S.47°W., 36 lks. scribed in the bark BT S29 T20S R8W. (Rec. bearing, S.50°W. 32 lks.)
 A fir, 40" dia., bears N.45°W., 46 lks., with illegible scribe marks visible on the bark. I reblaze below the orig. blaze & mark T20S R8W S20 BT. (Rec. 48 lks.)
and new BTs & reference monuments;
 An iron post, 3 ft. long, 2" dia., 28" in the ground for a reference monument, bears N.89°30'E., 10 lks., with brass cap marked T20S R8W S21 RM 1950 and an arrow pointing to the corner.
 A fir, 30" dia. bears S.61°E. 56 lks. mkd: T20S R8W S28 BT
 A fir, 56" dia., bears S.20½°W., 49 lks., mkd: T20S R8W S29 BT.
 An iron post, 3 ft. long, 2" dia., 28" in the ground for a reference monument, bears S.89°30'W., 10 lks., with brass cap marked T20S R8W S20 RM 1950 and an arrow pointing to the corner.

Fd. & used on BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12373)

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias	Description

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16740)

The cor. of secs. 20, 21, 28, & 29, occupied by the orig. corner tree, a burned fir, 32" dia., with healed blazes on the NE, SE, SW, & NW faces, from which the remains of the orig. BTs

A burned fir snag, 32" dia., bears N.60°E., 67 lks., with fragmentary scribe marks visible on decayed blaze.

A burned fir, 50" dia. bears S.47°W., 36 lks. with healed blaze.

A burned fir, 40" dia., bears N.45°W., 46 lks. with healed blaze.

and the remains of the BTs & reference monuments marked in 1950

An iron post, 2" dia., firmly set projecting 12" above ground for a reference monument, bears N.89½°E., 10 lks., with brass cap marked T20S R8W S21 RM 1950 and an arrow pointing to the corner.

A burned fir, 30" dia. bears S.61°E. 56 lks. with healed blaze.

A burned fir, 50" dia., bears S.20½°W., 49 lks., with healed blaze.

An iron post, 2" dia., firmly set projecting 12" above ground for a reference monument, bears S.89½°W., 10 lks., with brass cap marked T20S R8W S29 RM 1950 and an arrow pointing to the corner.

and an orig. line tree

A burned fir, 54" dia., bears S.4°17'W., 29 lks., with 2 healed blazes on the north & south faces.

Set a 5 ft. steel fence post alongside the iron post.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22959-60)

The cor. of secs. 20, 21, 28, & 29, monumented with the remains of the original cor. tree, a decayed fir stump, 34" dia., with no marks visible, from which the remains of the original bearing trees

A burned fir snag, 32" dia., bears N.60°E., 44.2 ft., with illegible scribe marks visible on partially healed blaze.

A burned decayed fir stump, 40" dia., bears S.47°W., 23.8 ft., no marks visible.

continued next page

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burned decayed fir stump, 42" dia., bears N.45°W., 30.4 ft., with scribe marks 20 and other illegible scribe marks visible on open blaze.

and accessories established by Tillman in 1950

An iron post, 2" dia., firmly set, projecting 14" above ground, bears N.87°13'20" E., 5.73 ft., with brass cap mkd. T20S R8W S21 RM 1950 and an arrow pointing to the cor. (Record, N.89½°E., 6.60 ft.)

A burned decayed fir stump, 23" dia., bears S.62¾°E., 26.1 ft., no marks visible. (Record, S.61°E., 37.0 ft.)

A burned decayed fir stump, 50" dia., bears S.20½°W., 32.3 ft., with a healed blaze.

An iron post, 2" dia., firmly set, projecting 9" above ground, bears S.86°14'00"W., 6.94 ft., with brass cap mkd. T20S R8W S201 RM 1950 and an arrow pointing to the cor. and with a steel fence post is alongside. (Record, S.89½°W., 6.60 ft.)

At the corner point
Saw the cor. tree stump flush with the surface of the ground on the uphill side and drive an aluminum rod, 10" long, 1/2" dia., 8" in the center of the stump, with aluminum cap mkd.

T20S	R8W
<u>S 20</u>	<u>S 21</u>
S 29	S 28
2011	

from which new bearing trees

A fir, 16" dia., bears S.80°E., 7.5 ft., mkd. T20S R8W S28 BT.

A fir, 15" dia., bears N.80¼°W., 8.7 ft., mkd. T20S R8W S20 BT.

From the corner E., 80 ft., spur ridge, slopes N. S., 395 ft., of the E. end of an overgrown dirt road, 20 ft. wide, bears S.10°E.
(Line tree - angle point: bears S.4°11'52"W., 18.14')

Ronald L Rice - For: Oxbow Timber 1 LLC - Jan. 2015 - M169-8

Found - 2011 BLM alum. cap with the following accessories:
42" D.Fir stump bears N.45°W., 30.4', scribing visible
1950 GLO brass cap bears N.87°13'20" E 5.73'
1950 GLO brass cap bears S.86°14'00" W 6.94'
23" D.Fir stump bears S.62¾°E., 26.1' - no marks
50" D.Fir stump bears S.20½°W., 32.3' - healed face
16" D.Fir bears S.80°E., 7.5' -healed face
15" D.Fir bears N.80¼°W., 8.7' - open face

Steel post adjacent to corner

cont.

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23189-90)

The cor. of secs. 20, 21, 28, and 29, monumented with an aluminum rod, 1/2" dia., firmly set, projecting 2" above the center of the remains of the original cor. tree, a decayed fir stump, 30" dia., with an aluminum cap mkd.

- from which the remains of the original bearing trees
 - A burned fir snag, 32" dia., bears N.60°E., 44.2 ft., with axe marks on the remains of a healed blaze.
 - A burned decayed fir stump, 39" dia., bears S.47°W., 23.8 ft., no marks visible.
 - A burned decayed fir stump, 41" dia., bears N.45°W., 30.4 ft., with scribe marks 8 S20 visible on open decayed blaze.

and the accessories established by Tillman in 1950
An iron post, 2" dia., firmly set, projecting 14" above ground, bears N.87°13'20"E., 5.73 ft., with brass cap mkd. T20S R8W S21 RM 1950 and an arrow pointing to the cor.

- A burned decayed fir stump, 23" dia., bears S.62¾°E., 26.1 ft., no marks visible.
- A burned decayed fir stump, 50" dia., bears S.20½°W., 32.3 ft., with a healed blaze.
- An iron post, 2" dia., firmly set, projecting 12" above ground, bears S.87°42'46"W., 6.94 ft., with brass cap mkd. T20S R8W S20 RM 1950 and an arrow pointing to the cor. A steel fence post is alongside. (Record, S.86°14'00"W.)

and the bearing trees mkd. by Forkner and Graham in 2011
A fir, 17" dia., bears S.80°E., 7.5 ft., with scribe marks T20S R8W S28 BT visible on pitchy partially healed blaze and a Mag Nail at the base on the right side center.
A fir, 16" dia., bears N.80¼°W., 8.7 ft., with scribe marks T20S R8W S20 BT visible on pitchy partially healed blaze and a Mag Nail at the base on the right side center.