

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 486)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked $\frac{1}{4}$ S on W face; from which
Fir, 20" dia., bears N.20°W., 36 lks., mkd: $\frac{1}{4}$ S BT.
Fir, 12" dia., bears S.50°E., 22 lks., mkd: $\frac{1}{4}$ S BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12376)

Point for the $\frac{1}{4}$ sec. cor. of secs. 16 & 17, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

$\frac{1}{4}$
S 17|S 16
1954

from which

A fir, 48" dia., bears S.54°E., 39 lks., mkd: $\frac{1}{4}$ S16 BT.
A fir, 55" dia., bears S.49 $\frac{1}{2}$ °W., 62 lks., mkd: $\frac{1}{4}$ S17 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16742-3)

The $\frac{1}{4}$ sec. cor. of secs. 16 & 17, determined at rec. bearing & dist. from the remains of the BTs marked in 1954

A sawed fir stump, 28" dia., bears S.54°E., 39 lks., with scribe marks $\frac{1}{4}$ S16 BT visible on open & burned blaze. Rescribed $\frac{1}{4}$ S16 BT on new blaze.

A sawed fir stump, 56" dia., bears S.49 $\frac{1}{2}$ °W., 62 lks., no marks remaining on decayed blaze.

At the corner point

Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, with brass cap marked:

T20S R8W
 $\frac{1}{4}$
S 17|S 16
1967

from which a new BT

A sawed fir stump, 48" dia., bears S.42°W., 80 lks., mkd: $\frac{1}{4}$ S17 BT.

Set a 6 ft. steel fence post alongside the iron post.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Robert Dean, LS 1808 & Wm. J. Ruppert, LS 866 - For:
International Paper Co. - 3/30/1983 - M93-80 & C.S. 58/204(N)

Found - 2" galv. IP w/3" BLM BC (per 1967 remonumentation)
mkd: T20S R8W ¼ S17 S16 1967, from which:
55" Fir stump bears S.50°12'W., 40.9 ft. (rec.
S.49½°W., 40.92 ft.) 1954 BT.
32" stump w/¼ S16 BT visible, bears S.55°11'E., 25.2
ft. (rec. S.54°E., 25.74 ft. 1954 BT.
New BTs- 4" D.Fir, scribed: ¼ S16 BT bears S.15°13'E. 11.0 ft
5" D.Fir, scribed: ¼ S17 BT bears S.50°22'W., 4.1 ft