

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 487)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked 1/4 S on W face; from which
Alder, 20" dia., bears N.86°E., 38 lks., mkd: 1/4 S BT.
Alder, 12" dia., bears N.27°W., 29 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12378-9)

The 1/4 sec. cor. of secs. 8 & 9 determined at rec. bearing & dist. from the orig. BTs:

A rotted alder stump, 36" dia., bears N.86°E., 38 lks., with no remaining marks.

An alder, 24" dia., bears N.27°W., 29 lks., with marks 1/4 S visible on partly healed blaze.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked

1/4
S 8 | S 9
1954

from which new BTs

A hemlock, 35" dia., bears S.22 1/4°E., 79 lks., mkd: 1/4 S9 BT

A fir, 40" dia., bears N.11°W., 76 lks., mkd: 1/4 S8 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16744)

The 1/4 sec. cor. of secs. 8 & 9, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remaining orig. BT

An Alder, 24" dia, bears N.27°W., 29 lks., no marks visible on partially healed blaze.

and the remains of the BTs marked in 1954

A sawed hemlock stump, 35" dia., bears S.22 1/4°E., 79 lks., with scribe marks 1/4 S9 BT visible on open blaze.

A fir, 45" dia., bears N.11°W., 76 lks. with healed blaze. and a new BT

A cedar, 12" dia., bears S.8 3/4°E., 70 lks., mkd: 1/4 S9 BT.

Set a 5 ft. steel fence post alongside the iron post.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21770)

The ¼ sec. cor. of secs. 8 and 9, monumented with an iron post, 1" dia., firmly set, projecting 1" above ground, with brass cap (properly) mkd. from which the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

A fir stump, 49" dia., bears N.11°W., 50.2 ft., with a burned healed blaze.

and the remains of a BT mkd. by Glenn, et al., in 1967

A cedar stump, 17" dia., bears N.8¾°E., 46.2 ft., with no marks visible on open burned blaze.

and new bearing trees

A fir, 11" dia., bears N.9¼°E., 22.4 ft., mkd. ¼ S9 BT.

A fir, 15" dia., bears S.54½°W., 15.0 ft., mkd. ¼ S8 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2670, Surveyed May 2012/June 2013 - (DCSO records Vol. 58 Pages 23045)

The ¼ sec. cor. of secs. 8 and 9, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd. from which the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

A burnt fir stump, 45" dia., bears N.11°W., 50.2 ft., with a healed blaze.

and the bearing trees mkd. by Graham in 2005

A fir, 11" dia., bears N.7½°E., 22.4 ft., with a healed blaze. (Record, N.9¼°E.)

A fir, 18" dia., bears N.54½°W., 15.0 ft., with a healed blaze.

A steel fence post is alongside cor.