

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Pages 487-8)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 8, 9, 4, & 5, mkd. T 20S S 4 on NE, R 8W S 9 on SE, S 8 on SW, S 5 on NW face, with 4 notches on E & 5 on S edge; from which

- Fir, 18" dia., bears N.63°E., 26 lks., mkd: T20S R8W S4 BT
- Fir, 16" dia., bears S.65°E., 33 lks., mkd: T20S R8W S9 BT
- Fir, 30" dia., bears S.35°W., 10 lks., mkd: T20S R8W S8 BT
- Fir, 20" dia., bears N.70°W., 17 lks., mkd: T20S R8W S5 BT

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12379)

The cor. of secs. 4, 5, 8, & 9, determined at rec. bearing & dist. from the orig. BTs:

- A fir, turned out, 19" dia., bears N.63°E., 26 lks., marked BT S4 T20S R8W.
- A fir, 22" dia., bears S.65°E., 33 lks., marked with a healed blaze.
- A fir, turned out, 40" dia., bears S.35°W., 10 lks., marked with a healed blaze.
- A fir, 24" dia., turned out, bears N.70°W., 17 lks., marked BT S5 T20S R8W.

At the corner point
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked

T20S R8W	
S 5	S 4
S 8	S 9
1954	

from which new BTs

- A fir, 23" dia. bears N.69°E., 48 lks. mkd: T20S R8W S4 BT
- A fir, 39" dia. bears S.13¼°W. 37 lks. mkd: T20S R8W S8 BT
- A fir, 28" dia. bears N.31½°W. 57 lks. mkd: T20S R8W S5 BT

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21771)

The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2" dia., firmly set, projecting 6" above the ground with brass cap (properly) mkd.
 from which the remains of an original bearing tree

- A decayed fir stump, 18" dia., bears S.65°E., 21.8 ft., with a healed blaze. continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

and the remains of BTs mkd. by Tillman, et al., in 1953-54
A fir stump, 35" dia., bears S.12°W., 24.4 ft., with scribe marks T20S R8W S8 BT visible on open blaze. (Record, S.13¼°W.)

A fir stump, 27" dia., bears N.31½°W., 40.2 ft., with illegible scribe marks visible on open blaze. (Record, 37.6 ft.)

and new bearing trees

A fir, 23" dia. bears N.63°E., 16.9 ft mkd. T20S R8W S4 BT

A fir, 19" dia. bears S.4°E., 31.8 ft mkd. T20S R8W S9 BT

A fir, 7" dia. bears S.42°W., 30.5 ft. mkd. T20S R8W S8 BT

A fir, 13" dia. bears N.57°W., 20.5 ft mkd. T20S R8W S5 BT

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

An iron pipe, 1½" dia., firmly set, projecting 6" above ground, established by person(s) unknown for unknown purpose is alongside the corner and was not utilized for control in this rehabilitation.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2670, Surveyed May 2012/June 2013 - (DCSO records Vol. 58 Pages 23045-6)

The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2½" dia., firmly set, projecting 6 ins. above ground (alongside of which is an iron pipe, 1½" dia., firmly set, projecting 8" above ground), with a brass cap (properly) mkd. from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears S.65°E., 21.8 ft., no marks visible.

and the remains of the BTs mkd. by Tillman, et al., in 1953-54

A fir stump, 35" dia., bears S.12°W., 24.4 ft., with scribe marks R8W S8 BT visible on open blaze.

A fir stump, 21" dia., bears N.29°W., 37.6 ft., with a healed blaze. (Record, N.31½°W., 40.2 ft.)

and the bearing trees mkd. by Graham in 2005

A fir, 24" dia., bears N.63°E., 15.3 ft., with a healed blaze. (Record, 16.9 ft.)

A fir, 22" dia., bears S.4°E., 31.8 ft., with a healed blaze.

A fir, 8" dia., bears S.42°W., 32.0 ft., with a healed blaze. (Record, 30.5 ft.)

A fir, 14" dia., bears N.57°W., 20.5 ft., with a healed blaze.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2809, surveyed Sept./Oct. 2015 - (DCSO records Vol. 58 Page(s) 23446-7 & Plat T20-8 2017-1)

The cor. of secs. 4, 5, 8, & 9, monumented with an iron post, 2" dia., firmly set, projecting 7" above ground (alongside of which is an iron pipe, 1½" dia., firmly set, projecting 7" above ground), with a brass cap (properly) mkd.

from which the remains of an original bearing tree
A decayed fir stump, size indeterminate, bears S.65°E., 21.8 ft., with no marks visible on pitch face and a healed blaze.

and the remains of the BTs mkd. by Tillman, et al. in 1953-54
A decayed fir stump, 33" dia., bears S.12°W., 22.2 ft., with scribe marks T2OS R8W S8 BT visible on open blaze. (Record, 24.4 ft.)

A decayed fir stump, 24" dia., bears N.29°W., 37.6 ft., with a healed blaze.

and the bearing trees mkd. by Graham in 2005
A fir, 26" dia., bears N.63°E., 15.3 ft., with a healed blaze and an embedded Mag Nail at the base on the right side center.

A fir, 24" dia., bears S.4°E., 31.8 ft., with a healed blaze.

A fir, 9" dia., bears S.42°W., 32.0 ft., with a healed blaze and an embedded Mag Nail at the base on the right side center.

A fir, 15" dia., bears N.57°W., 20.5 ft., with a healed blaze and an embedded Mag Nail at the base on the right side center.

An aluminum fence post is alongside the monument, which is located on the NE. cor. of a recently logged area, edge bears S. & W.

NAD 1983 (2011)
Latitude 43°50'56.81"N. Longitude 123°39'36.08"W.