

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & 4 of T21-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 452-53)

Set post 4" dia., 4 ft. long, with markd stone, 12" in ground for qr sec. cor. marked ¼ S on N. face; from which
Fir 30" dia., bears N.60°W., 33 lks. dist. mkd. ¼ S BT.
Alder 8" dia., bears S.32°W., 24 lks. dist. mkd. ¼ S BT.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11392-93)

The ¼ sec. cor., the locus of which is determined by reference to the record bearing and distance from the old SW. bearing tree.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

$$\frac{1}{4} \frac{S \ 33}{S \ 4}$$

1945

from which

An Alder 14" dia., bears S.32°W., 24 lks. dist. mkd. BT ¼ S. (Old BT)

A Fir 60" dia., bears N.18°45'E., 55 lks. dist. mkd. ¼ S33 BT. (New BT)

A Fir 48" dia., bears S.43½°W., 100 lks. dist. mkd. ¼ S4 BT. (New BT)

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16707)

The ¼ sec. cor., monumented with an iron post, 1" dia., firmly set, projecting 10" above ground with brass cap mkd. in 1945, from which the remaining original bearing trees:

An Alder 15" dia., bears S.37°W., 24 lks. dist., no marks remaining on burned blaze. (Rec. S.32°W.) Rescribed ¼ S4 BT on new blaze.

and the remains of the bearing trees mkd. in 1945:

A burned Fir stump 70" dia., bears N.18 ¾°E., 55 lks. dist., fragmentary scribe marks visible on burned blaze and a new bearing tree:

An Alder 6" dia., bears N.49½°W., 51½ lks. mkd. ¼ S33 BT.
Set a 5 ft. steel fence post alongside the iron post.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & 4 of T21-8

Alias	Description

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21745-6)

The ¼ sec. cor. of secs. 4 & 33, monumented with an iron post, 1" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd. from which the remains of a bearing tree mkd. by Price and Rigby in 1945

A fir snag, 70" dia., bears N.18¾°E., 36.3 ft., with scribe marks ¼ S33 BT visible on open burned blaze. and new bearing trees

A fir, 12" dia., bears S.67°E., 15.8 ft., mkd. ¼ S4 BT.

A fir, 11" dia., bears N. 1½° W., 20.0 ft., mkd. ¼ S33 BT. Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2285, surveyed Aug. 2009/ Feb. 2010 (DCSO records BLM plat 2011 & Vol. 56 Page(s) 22263-65)

The ¼ sec. cor. of sees. 4 & 33, on the N. bdy. of the Tp.. remonumented by Price and Rigby in 1945, rehabilitated by Glenn, et al., in 1967, and by Graham in 2005; monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with a brass cap (properly) mkd.

from which the remains of the BTs mkd. by Price and Rigby

A decayed burned fir snag, 62" dia., bears N.18¾°E., 36.3 ft. no marks visible.

A burned fir stump, 62" dia., bears S.43½°W., 66.0 ft., no marks visible.

and the remains of a BT mkd. by Glenn, et al.

An alder root collar, 33" dia., bears N.49½°W., 34.0 ft., no marks visible.

and the BTs mkd. by Graham

A fir, 13" dia., bears N.1/4°E., 20.0 ft., with a healed blaze. (Record, N.1½°W.)

A fir, 13" dia., bears S.64¾°E., 15.8 ft., with a healed blaze. (Record, S.67°E.)

A steel fence post is alongside the cor.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22970-1)

The ¼ sec. cor. of secs. 4 & 33, on the S. bdy. of the Tp., determined at record bearings and distances from the remains of the BTs mkd. by Price and Rigby in 1945 (Cont.)

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & 4 of T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A hollow decayed burned fir snag, 62" dia., bears N.18 $\frac{3}{4}$ °E.
36.3 ft., no marks visible.

A burned fir stump, 62" dia., bears S.43 $\frac{1}{2}$ °W., 66.6 ft., no
marks visible.

and the remains of a BT mkd. by Glenn, et al., in 1967

An alder root collar, 33" dia., bears N.49 $\frac{1}{2}$ °W., 34.0 ft.,
no marks visible.

and the bearing trees mkd. by Graham in 2005

A fir, 13" dia., bears N. 1/4°E., 20.0 ft., with a healed
blaze and an ingrown Mag Nail on the right side center.

A fir, 14" dia., bears S.64 $\frac{3}{4}$ °E., 15.8 ft., with a healed
blaze and an ingrown Mag Nail on the right side center.

At the corner point

Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the
ground, with brass cap mkd.

T20S R8W

$\frac{1}{4}$ $\frac{S\ 33}{S\ 4}$

T21S

2011

Deposit a magnet in a white plastic case at the base and
drive an aluminum angle iron, 5 ft. long, alongside of the
stainless steel post.