

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Pages 482-3)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked 1/4 S on N face; from which
Fir, 12" dia., bears N.23°W., 28 lks., mkd: 1/4 S BT.
Fir, 30" dia., bears S.10°E., 36 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11353)

Point for the 1/4 sec. cor. of secs. 28 & 33, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:
1/4 S 28
S 33
1950

from which
A fir, 48" dia., bears N.66 1/2°W., 25 lks., mkd: 1/4 S28 BT.
A fir, 48" dia., bears S.20°E., 64 lks., mkd: 1/4 S33 BT.

BLM remonumentation of Orig. corner points by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed June 1960 DCSO records Vol. 30 Page 12882-3

The 1/4 sec. cor. of secs. 28 & 33 was removed by the Bureau of Public Roads in 1958 while in the process of building an access road along the Smith River. At the time of their work they established reference points for the 1/4 sec. cor. These reference points were hubs set in line at points 300 ft & 500 ft NE'ly & 300 ft & 600 feet SE'ly from the corner. These points were subsequently recovered & the 1/4 sec. cor. reestablished from them.

At the corner point, which falls in the east edge of a curve of a graveled access road, 30 lks. wide, bearing NW & SE Set a steel shaft collar, 4" dia., 1 1/2" thick, with a 1 1/4" bore, 8" below the road surface. from which

An iron post, 28" long, 2 1/2" dia., set 22" in the ground for a reference monument, bears N.45°E., 130 lks., with brass cap mkd. 1/4 S28 RM 1960 & an arrow pointing to the corner.

A hemlock, 8" dia., bears S.54°E., 324 lks. mkd. 1/4 S33 BT.

An iron post, 28" long, 2 1/2" dia., set 24" in the ground for a reference monument, bears S.45°E., 130 lks., with brass cap mkd. 1/4 S 33 RM 1960 & an arrow pointing to the corner.

A maple, 8" dia., bears N.67°W., 131 lks., mkd. 1/4 S28 BT.

Cont.

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22958)

The ¼ sec. cor. of secs. 28 and 33, monumented with a square iron rod, 5/8 x 5/8", firmly set, with top on the E. edge and 12" below the surface of Smith River Road, asphalt surface, 20 ft. wide, bears N.20°W. and S.5°E., from which reference monuments established by Brooks in 1960

An iron post, 2½" dia., firmly set, projecting 7" above ground, bears N.46°49'54"E, 86.16 ft., with brass cap mkd. ¼ S28 RM 1960 and an arrow pointing to the cor. (Record, N.45°E., 85.80 ft.)

An iron post, 2½" dia., firmly set, with top flush with the surface of the ground, bears N.46°49'54"E, 86.16 ft., with brass cap mkd. ¼ S28 RM 1960 and an arrow pointing to the cor. (Record, N.45°E., 85.80 ft.) A steel fence post is alongside.

Latitude: 43°47'30.85"N. Longitude: 123°39'00.13"W.
NAD 1983 (CORS 96)