

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 484)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked 1/4 S on N face; from which
Fir, 30" dia., bears N.45°W., 21 lks., mkd: 1/4 S BT.
Hemlock, 20" dia., bears S.65°W., 34 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11356)

The 1/4 sec. cor. of secs. 21 & 28, determined at the record bearing & dist. from each of the orig. BTs as follow:

An uprooted hemlock, 20" dia., the stump hole of which bears S.65°W., 34 lks., with blaze decayed.

A uprooted fir, 48" dia., the stump hole of which bears N.45°W., 21 lks., with blaze healed.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked
1/4 $\frac{S\ 21}{S\ 28}$
1950

from which new BTs

A fir, 60" dia., bears N.30°E., 61 lks., mkd: 1/4 S21 BT.

A fir, 40" dia., bears S.26°W., 68 lks., mkd: 1/4 S28 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jolley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16740-1)

The 1/4 sec. cor. of secs. 21 & 28, determined at the record bearing the dist. from the remains of the BTs marked in 1950

A sawed fir stump, 62" dia., bears N.30°E., 61 lks., with scribe marks 1/4 S visible on partially healed blaze.

A sawed fir, 44" dia., bears S.26°W., 68 lks., no marks visible on decayed blaze.

At the corner point

Set an iron post, 14" long, 1" dia., 5" in drill hole, in solid rock, with brass cap mkd:
1/4 $\frac{S\ 21}{S\ 28}$
T20S R8W
1967

from which a new BT

A sawed cedar stump, 33" dia., bears S.29 1/2°W., 151 lks., mkd: 1/4 S28 BT.

Set a 5 ft. steel fence post alongside the iron post.

cont.

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias	Description

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21767)

The ¼ sec. cor. of secs. 21 and 28, monumented with an iron post, 1" dia., firmly set, flush with the ground, with brass cap (properly) mkd.

from which the remains of the BTs mkd. by Tillman in 1950
A fir stump, 58" dia., bears N.30°E., 40.3 ft., no marks visible.

A fir stump, 44" dia., bears S.26°W., 44.9 ft., no marks visible.

and the remains of a BT mkd. by Glenn, et al., in 1967
A cedar stump, 33" dia., bears S.29½°W., 99.7 ft., with a healed blaze.

and new bearing trees
A fir, 18" dia., bears N.36½°E., 37.2 ft., mkd. ¼ S21 BT.

A fir, 17" dia., bears S.10°W., 56.1 ft., mkd. ¼ S28 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22960-1)

The ¼ sec. cor. of secs. 21 & 28, monumented with an iron post, 1" dia., firmly set, projecting 1" above ground, with a brass cap, oriented E., (properly) mkd.

from which the remains of the BTs mkd. by Tillman in 1950
A fir stump, 58" dia., bears N.30°E., 40.3 ft., no marks visible.

A very decayed fir stump, size indeterminate, bears S.26°W., 44.9 ft., no marks visible. Remains partially buried in the fill bank of Smith River Road.

and the remains of a BT mkd. by Glenn, et al., in 1967
A decayed cedar stump, 36" dia., bears S.29½°W., 99.7 ft., no marks visible.

and the bearing trees mkd. by Graham in 2005
A fir, 23" dia., bears N.36½°E., 37.2 ft., with a healed blaze and a Mag Nail on the right side center.

A fir, 22" dia., bears S.10°W., 56.1 ft., with a healed blaze and a Mag Nail on the right side center.

A white Carsonite post is alongside the cor.
From the corner
S., 16.5 ft., centerline of Smith River Road, asphalt surface, 20 ft. wide, bears N.85°W. and S.85°E.
S. 40° E., 50 ft. a line crossing tag on a maple, 26" dia.