

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Pages 486-7)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Cedar, 20" dia., bears N.47°E., 11 lks., mkd: ¼ S BT.
Cedar, 20" dia., bears S.10°E., 30 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12377)

The ¼ sec. cor. of secs. 9 & 16 determined from the orig BTs:
A cedar, 30" dia., bears N.47°E., 11 lks., marked with a rotted blaze.
A cedar, 30" dia., bears S.10°E., 30 lks., marked with a healed blaze. (Rec. bearing S.10°E.)

At the corner point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked
¼ $\frac{S \ 9}{S \ 16}$
1954

from which a new BT
A cedar, 30" dia., bears N.67½°W., 36 lks., mkd: ¼ S9 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jolley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16743-4)

The ¼ sec. cor. of secs. 9 & 16, monumented with an iron post 1" dia., firmly set, projecting 10" above ground, with brass cap (properly) marked
from which the remaining orig. BT
A Cedar, 34" dia., S.10°W., 30 lks., with healed blaze.
and the BT marked in 1954
A cedar, 33" dia., bears N.67½°W., 36 lks., with healed blaze.
Set a 5 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21769-70)

The ¼ sec. cor. of secs. 9 and 16, monumented with an iron post, 1" dia., firmly set, in a collar of stone, projecting 6 ins. above the ground, with brass cap (properly) mkd. cont.

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an original bearing tree
A root hole bears S.10°W., 19.8 ft.
and the remains of a BT mkd. by Tillman, et al., in 1953-54
A root hole bears N.67½°W., 23.8 ft.
and new bearing trees
A fir, 10" dia., bears S.30¾°E., 44.3 ft., mkd. ¼ S16 BT.
An alder, 11" dia., bears N.70¾°W., 21.5 ft., mkd. ¼ S9 BT
on bark.
There is a steel fence post alongside the corner.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center.