

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 488)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which Alder, 24" dia., bears N.60°W., 30 lks., mkd: ¼ S BT. Fir, 24" dia., bears S.75°E., 13 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12380)

-----  
The ¼ sec. cor. of secs. 4 & 9 determined at rec. bearing & dist. from the orig. BTs:

A rotted cedar stump, 26" dia., bears N.60°W., 30 lks., with no marks remaining. (Rec. an alder)

A fir, 40" dia., bears S.75°E., 13 lks., with mark B and portions of other marks remaining on bark.

At the corner point

Set an iron post, 7" long, 1" dia., 6" in a sandstone boulder, 4x3x2 ft. above ground, with brass cap marked

\_\_\_\_\_ ¼  $\frac{S\ 4}{S\ 9}$   
1954

from which a new BTs

A fir, 58" dia., bears N.62½°E., 57 lks., mkd: ¼ S4 BT.

A cedar, 42" dia., bears S.46°E., 43 lks., mkd: ¼ S9 BT.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21771-2)

-----  
The ¼ sec. cor. of secs. 4 and 9, monumented with an iron post, 1" dia., firmly set, in a boulder 4x3x2 ft. above ground, with a brass cap (properly) mkd.

from which an original bearing tree

A fir, 46" dia., bears S.75°E., 8.6 ft., with no marks visible on open blaze.

and the remains of a BT mkd. by Tillman, et al., in 1953-54

A fir stump, 61" dia., bears N.62½°E., 37.6 ft., with no marks visible on burned partially healed blaze.

and a new bearing tree

A fir, 12" dia., bears N.15½°W., 5.6 ft., mkd. ¼ S4 BT.

There is a bent-over steel fence post alongside the corner. Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2809, surveyed Sept./Oct. 2015 - (DCSO records Vol. 58 Page(s) 23446-7 & Plat T20-8 2017-1)

-----

The ¼ sec. cor. of secs. 4 & 9, monumented with an iron post, 1" dia., firmly set, projecting 1" above a sandstone, 4x3x2 ft., with a brass cap (properly) mkd. from which an original bearing tree

A fir, 57" dia., bears S.75°E., 8.6 ft., with no marks visible on decayed partially healed blaze.

and the remains of a BT mkd. by Tillman, et al., in 1953-54

A fir stump, 61" dia., bears N.62½°E., 37.6 ft., with no marks visible on burned partially healed blaze.

and a bearing tree mkd. by Graham in 2005

A fir, 13" dia., bears N.15½°W., 5.6 ft., with a healed blaze & a Mag Nail at the base on the right side center Drive an aluminum angle iron on the E. side of the sandstone