

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 475)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Alder, 12" dia., bears N.80°E., 7 lks., mkd: ¼ S BT.
Alder, 18" dia., bears S.85°W., 3 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11345)

Point for the ¼ sec. cor. of secs. 33 & 34, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 33|S 34
1950

from which

A fir, 20" dia., bears S.85°E., 19 lks., mkd: ¼ S34 BT.
A fir, 16" dia., bears N.81°W., 21 lks., mkd: ¼ S33 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16731)

The ¼ sec. cor. of secs. 33 & 34, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.

from which the remains of the BTs mkd. in 1950

A burned fir, 20" dia., bears S.85°E., 19 lks., with healed blaze.

A burned fir, 16" dia., bears N.81°W., 21 lks., with healed blaze.

Set a 5 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21760)

The ¼ sec. cor. of secs. 33 and 34, monumented with an iron post, 1" dia., firmly set, projecting 9" above the ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Tillman in 1950

A decayed fir snag, 18" dia., bears S.85°E. 12.5 ft., with a healed blaze.

A decayed burned fir snag, 18" dia., bears N.81°W., 13.9 ft., with a healed blaze.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

and new bearing trees
A fir, 9" dia., bears N.71½°E., 12.2 ft., mkd. ¼ S34 BT.
A fir, 12" dia., bears S.34°W., 12.2 ft., mkd. ¼ S33 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct.. 2011 - (DCSO records Vol. 58 Page(s) 22954)

The ¼ sec. cor. of secs. 33 and 34, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd.
from which the remains of the BTs mkd. by Tillman in 1950
A decayed fir snag, 21" dia., bears S.85°E., 12.5 ft., with faint illegible scribe marks visible on remains of partially healed blaze.
A decayed burned fir snag, 13" dia., bears N.81°W., 13.9 ft., with remains of a healed blaze.
and the BTs mkd. by Graham in 2005
A fir, 10" dia., bears N.73½°E., 12.2 ft., with a healed blaze and an ingrown Mag Nail on the right side center. (Record, N.71½°E.)
A fir, 13" dia., bears S.34°W., 12.2 ft., with a healed blaze and an ingrown Mag Nail on the right side center.
A steel fence post is alongside the cor.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2780, surveyed March/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23443-5 & Plat T20-8 2016-1)

The ¼ sec. cor. of secs. 33 & 34, monumented with an iron post, 1" dia., firmly set, projecting 9" above ground. with a brass cap (properly) mkd.
from which the remains of the BTs mkd. by Tillman in 1950
A decayed fir snag, 20" dia., bears S.85°E., 12.5 ft., with scribe marks ¼ and other illegible scribe marks visible on partially healed blaze.
A decayed fir snag, 12" dia., bears N.81°W., 13.2 ft., with illegible scribe marks visible on falling-apart healed blaze. (Record. 13.9 ft.)
and the bearing trees mkd. by Graham in 2005
A fir, 11" dia., bears N.73½°E., 12.2 ft.. with a healed blaze. (Record, N.71½°E.)
A fir, 14" dia., bears S.34°W., 12.2 ft., with a healed blaze. A steel fence post is alongside the monument.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From the corner
N.5°29'46"E.. 300 ft., Marsh Creek Ridge Road, graveled
surface, 10 ft. wide, bears N.40°W. & S.35°E.

NAD 1983 (2011)
Latitude 43°47'04.99"N. Longitude 123°38'24.76"W.