

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Pages 475-6)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 28, 27, 33, & 34, mkd. T 20S S 28 on NE, R 8W S 34 on SE, S 33 on SW, S 27 on NW face, with 3 notches on E & 1 on S edge; from which

- Oak, 10" dia., bears N.49°E., 61 lks. mkd: T20S R8W S27 BT
- Fir, 12" dia., bears S.44°E., 62 lks. mkd: T20S R8W S34 BT
- Alder, 12" dia. bears S.45°W. 23 lks. mkd: T20S R8W S33 BT
- Fir, 10" dia., bears N.68°W., 35 lks. mkd: T20S R8W S28 BT

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Pages 11346)

The cor. of secs. 27, 28, 33, & 34, determined at the rec. bearing from the orig. NE, SE, & SW BTs & the rec. dist. from the orig. NW BT, as follows:

- A chinquapin, 18" dia., N.49°E., 51 lks., with blaze healed. (Rec. Oak, 61 lks.)
- A fir, 14" dia., bears S.44°E., 46 lks., with scribe marks destroyed when previously opened. (Rec., 62 lks.)
- A dogwood stool, bears S.45°W., 20 lks., with no blaze remaining. (Rec. an alder, 23 lks.)
- A fir, 16" dia., bears N.16½°W., 35 lks., with blaze healed. (Rec. bearing, N.68°W.)

At the corner point
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S	R8W
<u>S 28</u>	<u>S 27</u>
S 33	S 34
1950	

from which new BTs

- A fir, 20" dia. bears N.10°E. 61 lks. mkd: T20S R8W S27 BT
- A fir, 44" dia. bears S.61°E. 23 lks. mkd: T20S R8W S34 BT
- A madrona, 14" dia., bears S.19°W., 27 lks., mkd: T20S R8W S33 BT.
- A fir, 22" dia. bears N.21°W. 67 lks. mkd: T20S R8W S28 BT

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16731)

The cor. of secs. 27, 28, 33, & 34 monumented with an iron post, 2" dia., firmly set, projecting 14" above ground with brass cap (properly) mkd., from which the remains of the BTs mkd. in 1950

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 44" dia., bears S.61°E., 23 lks., no marks remaining on burned blaze. Rescribed T20S R8W S34 BT on new blaze.

A burned madrone snag, 7" dia., bears S.17°W., 25 lks., no marks remaining on burned blaze. (Rec. S.19°W., 27 lks.)

A burned fir stump, 22" dia., bears N.21°W., 67 lks., no marks remaining on burned blaze. Rescribed T20S R8W S28 BT on new blaze.

and a new BT

A burned cedar stump, 20" dia., bears N.47½°E., 50½ lks., mkd: T20S R8W S27 BT.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21760-1)

The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2" dia., firmly set, projecting 13" above the ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Tillman in 1950

A fir stump, 40" dia., bears S.61°E., 15.2 ft., no marks visible.

A burned fir stump, 24" dia., bears N.21°W., 44.2 ft., with scribe marks T20S and other illegible marks visible on open blaze.

and new bearing trees

A fir, 22" dia., bears N.½°E., 22.1 ft., mkd. T20S R8W S27 BT.

A fir, 11" dia., bears S.89¾°E., 41.6 ft., mkd. T20S R8W S34 BT.

A fir, 10" dia., bears S.38°W., 8.6 ft., mkd. T20S R8W S33 BT.

A fir, 15" dia., bears N.59¾°W., 15.5 ft., mkd. T20S R8W S28 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22954-5)

The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2" dia., firmly set, projecting 13" above ground, with a brass cap (properly) mkd.

from which the remains of an original BT recovered by Tillman in 1950

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A decayed fir stump, 4" dia., bears N.16½°W., 23.1 ft., no marks visible. Diameter is of the remaining heartwood. and the remains of the BTs mkd. by Tillman in 1950
A decayed fir stump, 32" dia., bears S.61°E., 15.2 ft., no marks visible.
A burned decayed fir stump, 23" dia., bears N.21°W., 45.5 ft., with scribe marks T20S R8W and other illegible scribe marks visible on open blaze. (Record, and to face, 44.2 ft.)
and the BTs mkd. by Graham in 2005
A fir, 22" dia., bears N.2°E., 22.1 ft., with a healed blaze and an ingrown Mag Nail on the right side center. (Record, N.1/2°E.)
A fir, 13" dia., bears S.89¾°E., 41.6 ft., with a healed blaze and an ingrown Mag Nail on the right side center.
A fir, 11" dia., bears S.38°W., 8.6 ft., with a healed blaze and an ingrown Mag Nail on the right side center.
A fir, 16" dia., bears N.59¾°W., 15.5 ft., with a healed blaze and an ingrown Mag Nail on the right side center.
A steel fence post is alongside the cor.
From the corner - N., 130 ft., spur ridge, slopes S.65°E.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2780, surveyed March/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23443-5 & Plat T20-8 2016-1)

The cor. of secs. 27, 28, 33, & 34, monumented with an iron post, 2" dia., firmly set, with a brass cap (properly) mkd. from which the remains of an original bearing tree
A decayed fir stump, 3" dia., bears N.16½°W., 23.1 ft., no marks visible.
and the remains of the bearing trees mkd. by Tillman in 1950
A decayed fir stump, 33" dia., bears S.61°E., 15.2 ft., no marks visible.
A burned decayed fir stump, size indeterminate, bears N.21°W., 45.5 ft., with scribe marks T20S R8W visible on open blaze.
and the bearing trees mkd. by Graham in 2005
A fir, 23" dia., bears N.2°E., 22.1 ft., with a healed blaze & a Mag Nail at the base on the right side center
A fir, 14" dia., bears S.89¾°E., 41.6 ft., with a healed blaze.
A fir, 11" dia., bears S.38°W., 8.6 ft., with a healed blaze & a Mag Nail at the base on the right side center
A fir, 18" dia., bears N.59¾°W., 15.5 ft., with a healed blaze.
A steel fence post is alongside the monument.