

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 477)

-----

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 21, 22, 27, & 28, mkd. T 20S S 22 on NE, R 8W S 27 on SE, S 28 on SW, S 21 on NW face, with 3 notches on E & 2 on South edge; from which

Alder, 14" dia. bears N.31°E. 33 lks. mkd: T20S R8W S22 BT

Chittem, 6" dia., bears S.42°E., 34 lks., mkd: T20S R8W S27 BT.

Chittem, 6" dia., bears N.34°W., 41 lks., mkd: T20S R8W S21 BT.

Alder, 14" dia., bears S.65°W., 12 lks., mkd: T20S R8W S28 BT.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11348)

-----

The cor. of secs. 21, 22, 27 & 28, located at the point of intersection of orig. blazed lines, duly identified.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S	R8W
<u>S 21</u>	<u>S 22</u>
S 28	S 27
1950	

from which

An Alder, 24" dia., bears N.45°E., 123 lks., mkd: T20S R8W S22 BT.

An Alder, 20" dia., bears S.46°E., 82 lks., mkd: T20S R8W S27 BT.

A Hemlock, 12" dia., bears S.31°W., 81 lks., mkd: T20S R8W S28 BT.

A Cedar, 42" dia., bears N.83½°W., 70 lks., mkd: T20S R8W S21 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jolley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16732-3)

-----

The cor. of secs. 21, 22, 27, & 28 monumented with an iron post, 2" dia., firmly set, projecting 8" above ground with brass cap (properly) mkd., from which the remains of the BTs mkd. in 1950

An alder snag, 15" dia., bears N.45°E., 123 lks., no marks remaining on burned blaze.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A burned alder snag, 14" dia., bears S.46°E., 82 lks., no marks remaining on burned blaze.  
A burned hemlock snag, 12" dia., bears S.31°W., 81 lks., no marks visible on open & burned blaze. Rescribed T20S R8W S28 BT on new blaze.  
A burned cedar snag, 42" dia., bears N.83½°W., 70 lks., with fragmentary scribe marks visible on burned blaze. Rescribed T20S R8W S21 BT on new blaze.  
and an unrecorded BT  
A burned hemlock, 11" dia., bears S.66°W., 63½ lks., no marks remaining on burned blaze.  
and new BTs  
A burned cedar snag, 45" dia., bears N.13°E., 175 lks., mkd: T20S R8W S22 BT.  
A burned fir, 45" dia., bears S.52°E., 251 lks., mkd: T20S R8W S27 BT.  
Set a 5 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21762-3)

-----  
The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, monumented with an iron post, 2" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd from which the remains of BTs mkd by Tillman in 1950  
A decayed hemlock snag, 14" dia., bears S.31°W., 53.5 ft., no marks visible.  
A cedar stump, 70" dia., bears N.83½°W., 46.2 ft., with no marks visible on open blaze.  
and the remains of a BT mkd. by Glenn, et al., in 1967  
A burned cedar snag, 44" dia., bears N.13°E., 115.5 ft., no marks visible.  
and new bearing trees  
A fir, 20" dia., bears N.80½°E., 22.8 ft., mkd. T20S R8W S22 BT.  
A fir, 21" dia., bears S.4½°E., 53.0 ft., mkd. T20S R8W S27 BT.  
A fir, 23" dia., bears S.41°W., 56.2 ft., mkd. T20S R8W S28 BT.  
A fir, 21" dia., bears N.31½°W., 109.9 ft., mkd. T20S R8W S21 BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Rice, NW Land Surveying - March 2013 - C.S. File 65/78-33  
-----

Condition report

Found - 1950 GLO brass cap with the following accessories:  
A decayed hemlock snag, 14" dia., bears S.31°W.,  
53.5 ft., no marks visible. (Found same)  
A cedar stump, 70" dia., bears N.83½°W., 46.2 ft.,  
no marks visible on open blaze. (Found same)  
A burned cedar snag, 44" dia., bears N.13°E., 115.5  
ft., no marks visible. (Found same)  
A fir, 20" dia., bears N.80½°E., 22.8 ft., mkd. T20S  
R8W S22 BT. (Now 24", healed face)  
A fir, 21' dia., bears S.4½°E., 53.0 ft., mkd. T20S  
R8W S27 BT. (Now 23", healed face)  
A fir, 23" dia., bears S.41°W., 56.2 ft., mkd. T20S  
R8W S28 BT. (Now 26", healed face)  
A fir, 21"dia., bears N.31½°W., 109.9 ft., mkd. T20S  
R8W S21 BT. (Now 24", healed face)

Note - Corner has steel post adjacent to it. All BTs have  
red painted bands and yellow tags.  
Compass Declination 16° East

Fd. as per M167-55 by R.Rice 2/2015 - C.S. File 65/88-2