

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 478)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked 1/4 S on W face; from which  
Hemlock, 9" dia., bears S.27°W., 15 lks., mkd: 1/4 S BT.  
Hemlock, 9" dia., bears S.26°E., 29 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11350)

-----  
Point for the 1/4 sec. cor. of secs. 21 & 22, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4  
S 21 | S 22  
1950

from which

A cedar, 22" dia., bears S.29°45'E., 17 lks. mkd: 1/4 S22 BT

A fir, 40" dia., bears S.61 1/2°W., 107 lks., mkd: 1/4 S21 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16734)

-----  
The 1/4 sec. cor. of secs. 21 & 22, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.

from which the remains of the BTs mkd. in 1950

A cedar, 26" dia., bears S.29 3/4°E., 17 lks., with scribe marks 1/4 S visible on partially healed blaze.

A root hole, bears S.61 1/2°W., 107 lks., with a down fir alongside, 40" dia. no marks remaining on burned blaze.

and a new BT

A fir stump, 48" dia. bears S.62°W. 132 lks. mkd: 1/4 S21 BT

Set a 6 ft. steel fence post alongside the iron post.

Ron Rice, NW Land Surveying - March 2013 - C.S. File 65/78-34

-----  
Found - 1950 GLO brass cap with the following accessories:

A cedar, 26" dia., bears S.29 3/4°E., 17 lks., with scribe marks 1/4 S visible on partially healed blaze. (Found 26" stump, burned face)

A root hole, bears S.61 1/2°W., 107 lks., with a down fir alongside, 40" dia. no marks remaining on burned blaze. (Not searched for)

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>New -</p>	<p>A fir stump, 48" dia. bears S.62°W., 132 lks. mkd: ¼ S21 BT (Now 48" burned, rotted stump, no marks)</p> <p>13" D.Fir bears S.18°W., 7.1 ft. - blazed, scribed ¼ S21 BT</p> <p>12" D.Fir bears N.28°W., 1.3 ft. - blazed, scribed ¼ S21 BT</p> <p>18" D.Fir bears N.70°E., 9.8 ft. - blazed, scribed ¼ S22 BT</p> <p>15" D.Fir bears S.17°E., 17.6 ft. - blazed, scribed ¼ S22 BT</p> <p>Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags. Compass Declination 16° East</p>