

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 479)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 9, 10, 15, & 16, mkd. T 20S S 10 on NE, R 8W S 15 on SE, S 16 on SW, S 9 on NW face, with 4 notches on S & 3 on E edge; from which

- Fir, 36" dia., bears N.36°W., 32 lks., mkd: T20S R8W S9 BT
- Fir, 36" dia., bears S.80°W., 47 lks. mkd: T20S R8W S16 BT
- Fir, 30" dia., bears S.31°E., 31 lks. mkd: T20S R8W S15 BT
- Fir, 20" dia., bears N.57°E., 27 lks. mkd: T20S R8W S10 BT

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12369-70)

The cor. of secs. 9, 10, 15, & 16, determined from the orig. BTs as follows:

- A rotted fir stump, 24" dia., bears N.57°E., 29 lks. with no marks remaining. (Rec. dist. 27 lks.)
- A fir snag, 30" dia., bears S.34°E., 31 lks., mkd BT S15 T20S R8W (Rec. bearing S.31°E.)
- A fir, 50" dia., bears S.80°W., 49 lks., mkd. BT S16 T20S R8W on bark (Rec. dist. 47 lks.)
- A fir, 50" dia., bears N.36°W., 35 lks., mkd. BT S9 T20S R8W on bark (Rec. dist. 32 lks.)

At corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S	R8W
S 9	S 10
S 16	S 15
1954	

from which new BTs

- A hemlock, 13" dia., bears N.78°E., 12 lks., mkd: T20S R8W S10 BT.
- A fir, 45" dia. bears S.30°E. 47 lks. mkd: T20S R8W S15 BT
- A hemlock, 8" dia., bears S.28½°W., 34 lks., mkd: T20S R8W S16 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16736)

The corner of secs. 9, 10, 15 & 16, monumented with an iron post, 2" dia., firmly set, projecting 8" above ground with brass cap (properly) mkd. continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

from which the remains of the orig. BTs
A burned fir, 50" dia., bears S.80°W., 49 lks., no marks visible on burned blaze. Rescribed T20S R8W S16 BT on new blaze.
A burned fir, 50" dia., bears N.36°W., 35 lks., no marks visible. Rescribed T20S R8W S9 BT on new blaze.
and the remains of the BTs marked in 1954
A burned & dead hemlock, 18" dia., bears N.78°E., 12 lks., no marks remaining on burned blaze. Rescribed T20S R8W S10 BT on new blaze.
A burned fir snag, 43" dia. bears S.30°E. 44 lks. no marks remaining on burned blaze. (Rec. 47 lks.) Rescribed T20S R8W S15 BT on new blaze.
A burned hemlock snag, 11" dia., bears S.28½°W., 34 lks., no marks remaining on burned blaze.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21764-5)

The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2" dia., firmly set, projecting 2" above the ground, with brass cap (properly) mkd.
From which the remains of the original bearing trees
A burned fir stump, 50" dia., bears S.80°W., 32.3 ft., with scribe marks T20S R8W S16 BT visible on open blaze.
A burned fir stump, 50" dia., bears N.36°W., 23.1 ft., with no marks visible on decayed blaze.
and the remains of a BT mkd. by Tillman, et al., in 1953-54
A burned fir stump, 43" dia., bears S.30°E., 31.0 ft., with scribe marks 20S R8W S15 BT visible on open blaze.
and new bearing trees
A fir, 12" dia., bears N.21¼°E., 6.6 ft., mkd. T20S R8W S10 BT.
A fir, 13" dia., bears S.40¼°E., 13.7 ft., mkd. T20S R8W S15 BT.
A fir, 15" dia., bears S.30½°W., 11.9 ft., mkd. T20S R8W S16 BT.
A fir, 12" dia., bears N.80°W., 5.9 ft., mkd. T20S R8W S9 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

continued next page

2

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias	Description

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2670, Surveyed May 2012/June 2013 - (DCSO records Vol. 58 Pages 23043)

The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2" dia., firmly set, projecting 4" above ground, with a brass cap (properly)mkd.

from which the remains of original bearing trees

A decayed fir stump, 50" dia., bears S.80°W., 32.3 ft., with axe marks visible on open blaze.

A decayed fir stump, 50" dia., bears N.36°W., 23.1 ft., no marks visible.

and the remains of a BT mkd. by Tillman, et al., in 1953-54

A fir stump, 43" dia., bears S.30°E., 31.0 ft., with scribe marks 20S R8W S15 BT visible on an open blaze.

and the bearing trees mkd. by Graham in 2005

A fir, 14" dia., bears N.21¼°E., 6.6 ft., with a healed blaze.

A fir, 17" dia., bears S.40¼°E., 13.7 ft., with a healed blaze.

A fir, 17" dia., bears S.27°W., 11.9 ft., with a healed blaze. (Record, S.30½°W.)

A fir, 14" dia., bears N.61¼°W., 5.9 ft., with a healed blaze. (Record, N.80°W.)

A steel fence post is alongside the cor.