

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Pages 480-1)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 4, 3, 9, & 10, mkd. T 20S S 3 on NE, R 8W S 10 on SE, S 9 on SW, S 4 on NW face, with 5 notches on S & 3 on E edge; from which

Fir, 40" dia., bears N.63°E., 58 lks., mkd: T20S R8W S3 BT
 Fir, 12" dia., bears S.10°E., 39 lks. mkd: T20S R8W S10 BT
 Fir, 36" dia., bears S.36°W., 25 lks. mkd: T20S R8W S9 BT
 Fir, 8" dia., bears N.55°W., 8 lks., mkd: T20S R8W S4 BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12371)

Point for the cor. of secs. 3, 4, 9, & 10, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R8W
<u>S 4 S 3</u>
S 9 S 10

1954

from which

A fir, 50" dia. bears N.47½°E. 51 lks. mkd: T20S R8W S3 BT
 A fir, 32" dia., bears S.78½°E., 51 lks., mkd: T20S R8W S10 BT.
 A fir, 60" dia., bears S.33°W., 111 lks., mkd: T20S R8W S9 BT.
 A fir, 50" dia. bears N.77°W., 60 lks. mkd: T20S R8W S4 BT

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jolley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16737)

The corner of secs. 3, 4, 9, & 10, monumented with an iron post, 1" dia., firmly set, projecting 18" above ground with brass cap (properly) mkd.

from which the BTs marked in 1954

A fir, 50" dia. bears N.47½°E. 51 lks., no marks remaining on burned blaze. Rescribed T20S R8W S3 BT on new blaze.
 A fir, 34" dia., bears S.78½°E., 51 lks. with healed blaze
 A fir, 60" dia., bears S.33°W., 111 lks., with burned blaze. Rescribed T20S R8W S9 BT on new blaze.
 A fir, 52" dia. bears N.77°W., 60 lks., with burned blaze. Rescribed T20S R8W S4 BT on new blaze.

CONT.

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Ronald L Rice - For: Oxbow Timber 1 LLC - Aug 2014 - M168-37

Found - GLO Brass cap dated 1954, pipe & cap found loose on the ground. Reset by distance-distance intersection from existing accessories. With the following accessories:

- 50" D.Fir stump bears N.47½°E., 33.7' - No marks
- 43" D.Fir bears S.78½°E., 33.7' - Healed face
- 60" D.Fir snag bears S.33°W., 74.5' (Record 73.3') - rotted face

Record 52" D.Fir bearing N.77°W., 60 lks. - down out of position

New BTs- 16" D.Fir bears N.66°W., 48.5' - Blazed, scribed T20S R8W S4 BT

18 D.Fir bears N.27°E., 63.1' -Blazed, scribed T20S R8W S3 BT

Ronald L Rice - For: Oxbow Timber 1 LLC - April 2016 - C.S. File 65/92-6

Found - GLO brass cap dated 1954 with the following accessories:

- 50" D.Fir stump bears N.47½°E., 33.7' - no marks
- 43" D.Fir bears S.78½°E., 33.7' - healed face.
- 60" D.Fir snag bears S.33°W., 74.5' (record 73.3') - rotted face

Record 52" D.Fir bearing N.77°W., 60 lks - down out of position.

16" D.Fir bears N.66°W., 48.5' - scribing visible

18" D.Fir bears N.27°E., 63.1' - scribing visible

11" D.Fir bears S.77°W., 27.3' - chopped " x" breast high blazed, scribed "BT" at base (recent BLM work)

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2809, surveyed Sept./Oct. 2015 - (DCSO records Vol. 58 Page(s) 23446-7 & Plat T20-8 2017-1)

The cor. of secs. 3, 4, 9, & 10, perpetuated by Rice, in 2014; monumented with an iron post, 2" dia., firmly set, projecting 19" above ground, in a collar of stone, with a brass cap (properly) mkd.

from which the remains of the BTs mkd. by Tillman, et al., in 1953-54

A fir stump, 53" dia., bears N.47½°E., 33.7 ft., no marks visible.

A fir, 41" dia., bears S.78½°E., 33.7 ft., with a healed blaze.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir snag, 60" dia., bears S.33°W., 73.3 ft., no marks visible.
and the bearing trees mkd. by Rice
A fir, 19" dia., bears N.26°E., 63.0 ft., with scribe marks T20S R8W S3 BT visible on partially healed blaze and a nail at the base on the right side center.
A fir, 17" dia., bears N.67½°W., 48.4 ft., with scribe marks T20S R8W S4 BT visible on partially healed blaze and a nail at the base on the right side center.
and a new bearing tree
A fir, 12" dia., bears S.77°W., 27.3 ft., mkd. X BT.
Corner is located on a rocky outcrop. Drive an aluminum angle iron 2 ft. NE. of the cor.