

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 481)</p> <p>-----</p> <p>Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; raised mound of stone alongside. No witness trees.</p>
<p>BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen &amp; Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12373)</p> <p>-----</p> <p>Point for the ¼ sec. cor. of secs. 3 &amp; 4, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:</p> <p style="text-align: center;">¼ S 4   S 3 1954</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 37" dia., bears S.66¼°E., 22 lks., mkd: ¼ S3 BT. A fir, 6" dia., bears N.28½°W., 14 lks., mkd: ¼ S4 BT.</p>
<p>BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, &amp; James E. Jelley, Cadastral Surveyors, under Group #s 350 &amp; 635, surveyed April &amp; May 1967 (DCSO records Vol. 43 Page(s) 16738)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 3 &amp; 4, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.</p> <p>from which the remains of the BTs marked in 1954</p> <p style="padding-left: 40px;">A fir, 37" dia., bears S.66¼°E., 22 lks., no marks remaining on burned blaze. Rescribed ¼ S3 BT on new blaze.</p> <p>and a new BT</p> <p style="padding-left: 40px;">A sawed fir stump, 60" dia., bears N.56°W., 16 lks., mkd: ¼ S4 BT.</p>
<p>BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21766)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 3 and 4, monumented with an iron post, 1" dia., firmly set, projecting 5" above the ground, with brass cap (properly) mkd.</p> <p>from which the remains of a BT mkd. by Tillman, et al in 1954</p> <p style="padding-left: 40px;">A fir stump, 38" dia., bears S.66¼°E., 14.5 ft., with illegible scribe marks visible on open blaze. cont.</p>

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of a BT mkd. by Glenn, et al., in 1967  
A fir stump, 60" dia., bears N.56°W., 10.6 ft., with  
scribe marks S ¼ BT visible on open blaze.  
and new bearing trees  
A fir, 13" dia., bears N.67½°E., 6.6 ft., mkd. ¼ S3 BT.  
A fir, 12" dia., bears S.87½°W., 9.8 ft., mkd. ¼ S4 Bt.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)  
driven at the base right side-center.

Fd. BC, 4 BTs and a steel posts by Ron Rice - 4/2014 - M168-3  
Fd. BC & all accessories by R. Rice - 4/2016 - C.S. 65/92-6