

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 15 & 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Pages 478-9)

-----  
Set post, 4" dia., 4 ft. long, in mound of stone, 18" high, 3½ ft. sq. at base, for qr. sec. cor. marked ¼ S on N face. No witness trees.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11351)

-----  
Point for the ¼ sec. cor. of secs. 15 & 22, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼  $\frac{S\ 15}{S\ 22}$   
1950

from which

A hemlock, 18" dia., bears N.40°E., 37 lks. mkd: ¼ S15 BT.

A maple, 16" dia., bears S.17°W., 19 lks., mkd: ¼ S22 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16735)

-----  
The ¼ sec. cor. of secs. 10 & 15, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.

from which the remains of the BTs mkd. in 1950

A burned hemlock, 21" dia., bears N.40°E., 37 lks., no mks remaining on burned blaze. Rescribed ¼ S15 BT on new blaze.

A burned maple, 16" dia., bears S.17°W., 19 lks., no marks remaining on burned blaze. Rescribed ¼ S22 BT on new blaze.

Set a 6 ft. steel fence post alongside the iron post.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2670, Surveyed May 2012/June 2013 - (DCSO records Vol. 58 Pages 23041-2)

-----  
The ¼ sec. cor. of secs. 15 & 22, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with a brass cap (properly) mkd. from which new bearing trees

A fir, 13" dia., bears S.64¼°E., 9.3 ft., mkd. ¼ S22 BT.

A fir, 17" dia., bears N.5°W., 12.8 ft., mkd. ¼ S15 BT.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 15 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Ron Rice, NW Land Surveying - April 2013 - C.S. File 65/78-29

-----  
Found - 1953 GLO brass cap with the following accessories:  
55" D.Fir snag bears N.54°W., 33.0 ft. - no marks  
36" D.Fir stump bears S.72°W., 48.2 ft. - no marks  
42" R.Cedar bears N.30°W., 52.8 ft. - healed face  
New - 43" R.Cedar bears N.89°W 11.4 ft. - blazed, scribed  
¼ S 15 BT.  
13" Alder bears S.40°E., 28.4 ft. - bark scribed ¼  
S22 BT  
Note - Corner has steel post adjacent to it. All BTs have  
red painted bands and yellow tags.  
Decl. 16°E.