

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 470)

-----  
Set post 4" dia., 4 ft. long, in mound of stone, 18" high, 3 ft. sq. at base, for qr. sec. cor. marked ¼ S on W face.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO records Vol. 27 Page(s) 11339-40)

-----  
Point for the ¼ sec. cor. of secs. 34 & 35, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼  
S 34|S 35  
1950

from which

- A fir, 34" dia., bears N.66°E., 29 lks., mkd: ¼ S35 BT.
- A fir, 24" dia., bears N.46°W., 12 lks., mkd: ¼ S34 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16724)

-----  
The ¼ sec. cor. of secs. 34 & 35, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.

from which the remains of the trees marked in 1950

- A burned fir snag, 33" dia., bears N.66°E., 29 lks., with healed blaze.
- A burned & dead fir, 26" dia., bears N.46°W., 12 lks., with healed blaze.

Set a 6 ft. steel fence post alongside the iron post.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2780, surveyed March/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23443-5 & Plat T20-8 2016-1)

-----  
The ¼ sec. cor. of secs. 34 & 35, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with a brass cap (properly) mkd.

from which the remains of the BTs mkd. by Tillman in 1950

- A burned decayed fir stump, 30" dia., bears N.66°E., 19.1 ft., no marks visible.
- A burned decayed fir stump, 26" dia., bears N.46°W., 7.9 ft., with a healed blaze.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees  
A fir, 22" dia., bears N.29½°E., 20.4 ft. mkd. ¼ S35 BT.  
A fir. 11" dia., bears N.55¼°W., 14.7 ft. mkd. ¼ S34 BT &  
a Mag Nail driven at the base on the left side center.  
A steel fence post is alongside the monument.  
NAD 1983 (2011)  
Latitude 43°47'03.72"N. Longitude 123°37'14.17"W.