

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 472)

-----  
Set post, 6" dia., 4 ft. long, in mound of stone, 18" high, 3 ft. sq. base, for cor. to secs. 14, 15, 22, & 23, marked T20S S14 on NE, R8W S23 on SE, S22 on SW, S15 on NW face, with 2 notches on S & E edges. No witness trees.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol 27 Pages 11344-5)

-----  
The cor. of secs. 14, 15, 22, & 23, monumented with the decayed remains of a wooden post, lying in a small mound of stone, located on a blazed line extending N & S duly identified.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S	R8W
<u>S 15</u>	<u>S 14</u>
S 22	S 23
1950	

from which

A Maple, 24" dia., bears N.26°E., 76 lks., mkd: T20S R8W S14 BT.

A Fir, 54" dia., bears S.51½°E., 87 lks., mkd: T20S R8W S23 BT.

A Fir, 48" dia., bears S.13°45'W., 161 lks., mkd: T20S R8W S22 BT.

A Fir, 50" dia., bears N.79°W., 91 lks., mkd: T20S R8W S15 BT.

Fd. & used on BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO records Vol. 27 Page(s) 11363)

Fd. & used on BLM dependent resurvey by Thomas A. Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12363)

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16727)

-----  
The cor. of secs. 14, 15, 22, & 23, monumented with an iron post, 2" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.  
continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of the BTs marked in 1950  
A burned & sawed fir stump, 52" dia., bears S.13¾°W., 161 lks., with fragmentary scribe marks visible on partially healed & burned blaze. Rescribed T20S R8W S22 BT on new blaze.  
A root hole, bears N.79°W., 91 lks., with a down & burned fir alongside, 52" dia., no marks remaining on burned blaze.  
and new BTs  
A burned & sawed fir stump, 62" dia., bears N.25½°E., 103½ lks., mkd: T20S R8W S14 BT.  
A burned & sawed fir stump, 60" dia., bears S.68½°E., 164 lks., mkd: T20S R8W S23 BT.  
A burned fir, 62" dia., bears N.78½°W., 163 lks., mkd: T20S R8W S15 BT.  
Set a 6 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21759-60)

-----  
The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2" dia., firmly set, projecting 3" above the ground, with brass cap (properly) mkd.  
from which the remains of a BT mkd. by Tillman in 1950  
A burned decayed fir stump, 50" dia., bears S.13¾°W., 106.3 ft., no marks visible.  
and the remains of BTs mkd. by Glenn, et al., in 1967  
A burned fir stump, 50" dia., bears N.25½°E., 68.3 ft., no marks visible.  
A burned fir stump, 53" dia., bears S.68½°E., 108.2 ft., with a healed blaze.  
A burned fir stump, 50" dia., bears N.78½°W., 107.6 ft., with a healed blaze.  
and new bearing trees  
A fir, 17" dia., bears N.34¾°E., 20.5 ft., mkd. T20S R8W S14 BT.  
A fir, 17" dia., bears S.84¼°E., 113.3 ft., mkd. T20S R8W S23 BT.  
A fir, 14" dia., bears S.13°W., 74.5 ft., mkd. T20S R8W S22 BT.  
An alder, 8" dia., bears N.84°W., 31.8 ft., mkd. T20S R8W S15 BT on bark.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Ron Rice - March 1, 2013 - C.S. File 65/78-15

-----  
Condition Report

Found - 1954 GLO brass cap with the following accessories:  
A burned decayed fir stump, 50" dia. bears S.13 $\frac{3}{4}$ °W.,  
106.3 ft., no marks visible. (Found same)  
and the remains of BTs mkd. by Glenn, et al., in 1967  
A burned fir stump, 50" dia., bears N.25 $\frac{1}{2}$ °E.,  
68.3ft., no marks visible. (Found same)  
A burned fir stump, 53" dia., bears S.68 $\frac{1}{2}$ °E., 108.2  
ft., with a healed blaze. (Found same)  
A burned fir stump, 50" dia., bears N.78 $\frac{1}{2}$ °W., 107.6  
ft., with a healed blaze. (Found same)  
A fir, 17" dia., bears N.34 $\frac{3}{4}$ °E., 20.5 ft., mkd. T20S  
R8W S14 BT. (Found 19" with healed face)  
A fir, 17" dia., bears S.84 $\frac{1}{4}$ °E., 113.3 ft., mkd.  
T20S R8W S23 BT. (Found 21" with healed face)  
A fir, 14" dia., bears S.13°W., 74.5 ft., mkd. T20S  
R8W S22 BT. (Found 16" with healed face)  
An alder, 8" dia., bears N.84°W., 31.8 ft., mkd T20S  
R8W S15 BT on bark. (Fd 8" with bark scribing  
visible)

Note - Location & Comments Corner has steel post adjacent  
to it. All BTs have red painted bands and yellow  
tags.

Declination 16° East

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral  
Surveyor, under Group No. 2670, Surveyed May 2012/June 2013 -  
(DCSO records Vol. 58 Pages 23040-1)

-----  
The cor. of secs. 14, 15, 22, and 23, monumented with an iron  
post, 2" dia., firmly set, projecting 5" above ground, with  
a brass cap oriented northwesterly, (properly) mkd.  
from which the remains of a BT mkd. by Tillman in 1950

A decayed fir stump, size indeterminate, bears S.13 $\frac{3}{4}$ °W.,  
106.3 ft., no marks visible.  
and the remains of the BTs mkd. by Glenn, et al., in 1967  
A burnt fir stump, 50" dia., bears N.25 $\frac{1}{2}$ °E., 68.3 ft., no  
marks visible.  
A burnt fir stump, 53" dia., bears S.68 $\frac{1}{2}$ °E., 108.2 ft., no  
marks visible.  
A burnt, decayed fir stump, 50" dia., bears N.78 $\frac{1}{2}$ °W.,  
107.6 ft., with axe marks.  
and the bearing trees mkd. by Graham in 2005  
A fir, 19" dia., bears N.34 $\frac{3}{4}$ °E., 20.5 ft., with a healed  
blaze.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 21" dia., bears S.84¼°E., 113.3 ft., with a healed blaze.

A fir, 15" dia., bears S.13°W., 74.5 ft., with a healed blaze.

An alder, 9" dia., bears N.84°W., 31.8 ft., with scribe marks T20S R8W S15 BT visible on bark.

NAD 1983 (2011)

Latitude: 43°49'16.02"N. Longitude: 123°37'12.64"W.