

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 473)

-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 10, 11, 14, & 15, mkd. T 20S S 11 on NE, R 8W S 14 on SE, S 15 on SW, S 10 on NW face, with 4 notches on S & 2 on E edge; from which  
Fir, 8" dia., bears N.20°E., 27 lks. mkd: T20S R8W S11 BT.  
Fir, 6" dia., bears S.25°E., 40 lks. mkd: T20S R8W S14 BT.  
Fir, 9" dia., bears S.60°W., 50 lks. mkd: T20S R8W S15 BT.  
Fir, 10" dia., bears N.72°W., 62 lks. mkd: T20S R8W S10 BT

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12364-5)

-----  
Point for the cor. of secs. 10, 11, 14, & 15, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:  
T20S R8W  
S 10 | S 11  
S 15 | S 14  
1954

from which  
An alder, 9" dia., bears N.5½°E., 12 lks. marked T20S R8W S11 BT.  
A fir, 24" dia., bears S.31¾°E., 7 lks., marked T20S R8W S14 BT.  
A fir, 15" dia., bears S.30°W., 42 lks., mkd: T20S R8W S15 BT.  
A fir, 15" dia., bears N.68½°W., 38 lks., mkd: T20S R8W S10 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16728-9)

-----  
The corner of secs. 10, 11, 14, & 15, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground with brass cap (properly) mkd.  
from which the remains of the BTs marked in 1954  
An alder, 9" dia., bears North, 12 lks., with scribe marks T20S R8W S11 BT visible on bark. (Rec. N.5½°E.)  
A fir, 20" dia., bears S.31¾°E., 7 lks. with healed blaze.  
A fir, 17" dia., bears S.30°W., 42 lks., with healed blaze  
continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 17" dia. bears N.68½°W., 38 lks. with healed blaze.  
and a new BT

A fir, 20" dia., bears N.43½°E., 27 lks., mkd: T20S R8W  
S11 BT.

Les Roberts, LS 1039 - For: I.P. - Jan. 1993 - M116-53 - C.S.  
File 63/149-9

-----  
Found - 1954 GLO brass cap set firmly in the ground.  
20" Fir stump, S.30°W., 27.5' (scar vis.) rec.  
S.30°W., 27.7' (1954 BT)  
22" Fir stump, S.32°E., 4.5' (scar vis) rec.  
S.31¾°E., 4.6' (1954 BT)  
40" Fir, N.43°E., 18.0' (scar vis.) Rec. 43½°E.,  
17.8' (1967 BT)  
New BTs- 8" Alder, N.89°E., 23.6', scribed/painted red.  
8" Alder, West, 22.4' scribed/painted red.  
9" Alder, N.59°E., 16.6' scribed/painted red.  
Note - Corner lies on SW slope about 120' West of spur  
ridge. Ridge bears N.10°W., & S.10°E.

Ronald L Rice - For: Oxbow Timber 1 LLC - Aug 2014 - M168-37

-----  
Found - GLO Brass cap dated 1954 with the following  
accessories:  
46" D.Fir bears N.43°E., 18.0' - healed face  
10" Alder bears N.89°E., 23.6' - bark scribe visible  
14" Alder bears west 22.4' - bark scribe visible  
12" Alder bears N.59°W., (Record N.59°E.) 16.6' -  
bark scribe visible  
Other accessories of record not searched for  
Steel and aluminum posts adjacent to corner