TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 474)

---

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 10" dia., bears S.42°W., 95 lks., mkd: ¼ S BT.
Fir, 15" dia., bears N.63°E., 101 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12366)

---

Point for the ¼ sec. cor. of secs. 10 & 11, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked: ¼
S 10|S 11
1954
from which
An alder, 10" dia., bears N.41¼°E., 23 lks. mkd: ¼ S11 BT.
A fir, 28" dia., bears S.36°W., 54 lks., mkd: ¼ S10 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16729)

---

The ¼ sec. cor. of secs. 10 & 11, monumented with an iron post, 1" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.
from which BTs mkd. in 1954
An alder, 14" dia., bears N.41¼°E., 21 lks., with scribe marks 1 BT visible on bark. (Rec. 23 lks.)
A fir, 34" dia., bears S.36°W., 54 lks., with healed blaze. Rescribed ¼ S10 BT on new blaze.
and a new BT
A fir, 48" dia., bears N.26°E., 65 lks., mkd: ¼ S11 BT.