

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 474)  
 -----  
 Set post, 6" dia., 4 ft. long, in mound of rocks, 18" high, 3 ft. sq. at base, for cor. to secs. 2, 3, 10, & 11, mkd. T 20S S 2 on NE, R 8W S 11 on SE, S 10 on SW, S 3 on NW face, with 5 notches on S & 2 on East edge. No witness trees.

---

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12366-7)  
 -----  
 Point for the cor. of secs. 2, 3, 10, 11, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S	R8W
<u>S 3</u>	<u>S 2</u>
S 10	S 11

1954 from which

- A fir, 33" dia. bears N.70°E., 30 lks. mkd: T20S R8W S2 BT
- A fir, 65" dia., bears S.45¾°E., 29 lks., mkd: T20S R8W S11 BT.
- A fir, 34" dia., bears S.48°W., 22 lks., mkd: T20S R8W S10 BT.
- A fir, 42" dia. bears N.56¾°W. 18 lks. mkd: T20S R8W S3 BT

---

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jolley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16729-30)  
 -----  
 The cor. of secs. 2, 3, 10, & 11, monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.  
 from which the remains of the BTs marked in 1954

- A dead fir, 36" dia., bears N.70°E., 30 lks., with healed blaze.
- A fir snag, 66" dia., bears S.45¾°E., 29 lks., no marks remaining on burned blaze. Rescribed T20S R8W S11 on new blaze.
- A fir snag, 36" dia., bears S.48°W., 22 lks., no marks remaining on burned blaze. Rescribed T20S R8W S10 BT on new blaze.
- A fir snag, 46" dia., bears N.56¾°W., 18 lks., no marks remaining on burned blaze. Rescribed T20S R8W S3 BT on new blaze.

Cont.

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald L Rice - For: Oxbow Timber 1 LLC - Aug 2014 - M168-37  
-----

Found - GLO Brass cap dated 1954 with the following accessories:  
36" D.Fir stump bears N.70°E., 19.8' - scribing visible  
66 D.Fir stump bears S.45¾°E., 19.1' - scribing visible  
36" D.Fir stump bears S.48°W., 14.5' - scribing visible  
46" D.Fir stump bears N.56¾°W., 11.9' - scribing visible  
New BTs- 12" D.Fir bears N.6°E., 26.6' - blazed, scribed T20S R8W S2 BT  
12" D.Fir bears S.62°E., 11.4' - blazed scribed T20S R8W S11 BT  
17" D.Fir bears S.1°W., 13.8" - blazed, scribed T20S R8W S10 BT  
8" D.Fir bears N.80°W., 5.4' - blazed, scribed T20S R8W S3 BT  
Steel post adjacent to corner