

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 475)</p> <p>-----</p> <p>Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked <math>\frac{1}{4}</math> S on W face; from which Fir, 3" dia., bears N.82°E., 69 lks., mkd: <math>\frac{1}{4}</math> S BT. Fir, 6" dia., bears S.81°E., 72 lks., mkd: <math>\frac{1}{4}</math> S BT.</p>
<p>BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen &amp; Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12368)</p> <p>-----</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 2 &amp; 3, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S 3   S 2 1954</p> <p>from which A fir, 16" dia., bears N.30°E., 15 lks., mkd: <math>\frac{1}{4}</math> S2 BT. A fir, 18" dia., bears S.60°W., 10 lks., mkd: <math>\frac{1}{4}</math> S3 BT.</p>
<p>BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, &amp; James E. Jelley, Cadastral Surveyors, under Group #s 350 &amp; 635, surveyed April &amp; May 1967 (DCSO records Vol. 43 Page(s) 16730)</p> <p>-----</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 2 &amp; 3, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which BTs mkd. in 1954 A fir, 19" dia., bears N.50°E., 15 lks. with healed blaze. (Rec., N.30°E.) A fir, 23" dia., bears S.83°W., 10 lks. no marks remaining on burned blaze. (Rec. S.60°W.) Rescribed <math>\frac{1}{4}</math> S3 BT on new blaze.</p>
<p>David Edwards - For: Oxbow Timber 1 LLC - 1/2015 - M170-32</p> <p>-----</p> <p>Found - BLM brass cap All previous BTs gone. New BTs- 10" Fir scribed "<math>\frac{1}{4}</math> S2 BT" bears N.77°E., 17.9' 13" Fir scribed "<math>\frac{1}{4}</math> S3 BT" bears N.74°W., 13.3'</p>
<p>Fd as per rec. by D Edwards 4/2019, M175-39</p>