

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2, T21-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 454)

A Fir 6" dia. for qr. sec. cor., marked ¼ S on N. face, from which

Fir 4" dia., bears N.30°W., 23 lks. dist. mkd. ¼ S BT.

Fir 6" dia., bears S.45°W., 15 lks. dist. mkd. ¼ S BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #292, Surveyed June/Oct. 1950 - (DCSO records Vol. 27 Page(s) 11327)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

¼  $\frac{S\ 35}{S\ 2}$   
1950

from which

A Fir 12" dia., bears N.16°E., 41 lks. dist. mkd. ¼ S35 BT.

A Fir 24" dia., bears S.83½°W., 19 lks. dist. mkd. ¼ S2 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16704-05)

The ¼ sec. cor., monumented with an iron post 1" dia., firmly set, projecting 10" above ground, with brass cap mkd. in 1950 from which the remains of the bearing trees mkd. in 1950:

A burned and dead Hemlock 15" dia., bears N.16°E., 41 lks. dist., with scribe marks 1/4 S35 BT visible on open blaze. (Rec. Fir)

A burned Fir 24" dia., bears S.83½°W., 19 lks. dist. with healed blaze.

Set a 6 ft. steel fence post alongside the iron post.

BLM survey by Joel E. Robb, Cadastral Surveyor, under Group #1171, surveyed Aug/Sept. 1983 - (DCSO records Vol. 46 Page(s) 17803)

The ¼ sec. cor., monumented with an iron post 1" dia., firmly set, projecting 4" above ground with brass cap mkd. in 1950, from which the remains of bearing trees mkd. by Tillman:

(Cont. Next Page)

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Hemlock snag, 13" dia., bears N.16°E., 41 lks. dist., with scribe marks  $\frac{1}{4}$  S35 BT visible on open blaze.  
A Fir 26" dia., bears S.83½°W., 19 lks. dist., with healed blaze.  
and a new bearing tree:  
A Fir 4" dia., bears N.2½°W., 58½ lks. dist. mkd. X BT.