

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 471)

-----  
 Set post 4" dia., 4 ft. long, in mound of stone, 18" high, 3 ft. sq. at base, for gr. sec. cor. marked 1/4 S on N face. No witness trees.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11343)

-----  
 Point for the 1/4 sec. cor. of secs. 23 & 26, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4    S 23  
           S 26  
           1950

from which

- A fir, 12" dia., bears N.76 1/4°W., 34 lks., mkd: 1/4 S23 BT.
- A hemlock, 22" dia. bears S.13 1/2°E., 31 lks. mkd: 1/4 S26 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16726)

-----  
 The 1/4 sec. cor. of secs. 23 & 26, monumented with a iron post, 1" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.

from which the remains of the BTs marked in 1950

A burned fir snag, 20" dia., bears N.76 1/4°W., 34 lks., with healed blaze.

A burned & sawed hemlock stump, 32" dia., bears S.13 1/2°E., 31 lks., with healed blaze.

Set a 6 ft. steel fence post alongside the iron post.

Ronald L. Rice, Ward NW Inc. - Jason Collier - Feb. 13, 2012 - C.S. File 65/76-15 & M167-69 (3/2014)

-----  
 Found - BLM brass cap, 1950, w/the following accessories:  
           12" D.Fir stump bears N.76 1/4°W., 22.4' - scribing visible

          22" Rotted Hemlock stump bears S.13 1/2°E., 20.5' - rotted face

New - 15" D.Fir bears S.41°W., 17.3' - blazed, scribed "1/4 S26 BT"

          15" D.Fir bears S.29°E., 17.8' - blazed, scribed "1/4 S26 BT"

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

14" D.Fir bears N.4°W., 8.6' - blazed, scribed "¼  
S23 BT"  
10" D.Fir bears N.79°W., 8.6' - blazed, scribed "¼  
S23 BT"  
Note - Corner has steel post adjacent to it. All BTs have  
red painted bands and yellow tags.  
Compass Declination 16° East