TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 474)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Fir, 12" dia., bears S.41°E., 101 lks., mkd: ¼ S BT.
Fir, 16" dia., bears N.19°W., 92 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12367)

Point for the ¼ sec. cor. of secs. 2 & 11, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ S 2 / S 11 / 1954

from which
A fir, 15" dia., bears N.16°W., 28 lks., mkd: ¼ S2 BT.
A fir, 20" dia., bears S.40¼°W., 59 lks., mkd: ¼ S11 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16730)

The ¼ sec. cor. of secs. 2 & 11, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.
from which BTs mkd. in 1954
A fir, 20" dia., bears N.16°W., 28 lks. with healed blaze.
A fir, 23" dia. bears S.40¼°W., 59 lks. with healed blaze.
Set a 6 ft. steel fence post alongside the iron post.

David Edwards - For: Roseburg Resources -April 2019 - M175-39

Found - Brass cap
38" fir bears S.40¼°W., 38.9'
36" fir bears N.16°W., 18.5'
Both with healed blaze
Set - A 6' steel post 2 ft N.1°E.