

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T21-8

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 454)

 Set post 6" dia., 4 ft. long, with marked stone 12" in ground, for cor. to secs. 1, 2, 35 & 36, marked T20S S36 on NE.; R8W S1 on SE.; T21S S2 on SW.; S35 on NW. faces, with 5 notches on W. & 1 on E. edges; from which
 Laurel 10" dia., bears N.50°E., 27 lks. dist. mkd. T20S R8W S36 BT.
 Fir 30" dia., bears S.50°E., 11 lks. dist. mkd. T21S R8W S1 BT.
 Fir 30" dia., bears S.41°W., 61 lks. dist. mkd. T21S R8W S2 BT.
 Fir 40" dia., bears N.87°W., 80 lks. dist. mkd. T20S R8W S35 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #292, Surveyed June/Oct. 1950 - (DCSO records Vol. 27 Page(s) 11326)

 The sec. cor., determined at the record bearing and distance from the original NE. and SE. bearing trees, and the record bearing from the original SW. and NW. bearing trees, as follows:

- A Madrona stump 12" dia., bears N.50°E., 27 lks. dist. with blaze entirely decayed.
- An uprooted Fir 30" dia., the stump hole of which bears S.50°E., 11 lks. dist. mkd. BT T21S R8W S1.
- A Fir snag 30" dia., bears S.41°W., 58 lks. dist. with the scribe marks R8 visible on the decayed blaze. (Rec., 61 lks. dist.)
- A Fir snag 40" dia., bears N.87°W., 68 lks. dist. mkd. BT S35 T20S R8W. (Rec. 80 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S	R 8 W
S 35	S 36
S 2 S 1	
T 21 S	
1950	

from which new bearing trees:

- A Fir 24" dia., bears N.60°E., 47 lks. dist. mkd. T20S R8W S36 BT.
- A Fir 18" dia., bears S.44¼°E., 22 lks. dist. mkd. T21S R8W S1 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T21-8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

A Fir 14" dia., bears S.39°W., 18 lks. dist. mkd. T21S R8W S2 BT.
A Fir 10" dia., bears N.34¼°W., 19 lks. dist. mkd. T20S R8W S35 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16704)

The sec. cor. monumented with an iron post 2" dia. firmly set, projecting 10" above ground with brass cap mkd. in 1950, from which the remains of the original bearing trees:
A burned Fir stump 20" dia., bears S.41°W., 58 lks. dist., no marks remaining.
A Fir snag 35" dia., bears N.87°W., 68 lks. dist., no marks remaining on burned blaze.
and the remains of the bearing trees mkd. in 1950:
A burned and dead Fir 32" dia., bears N.60°E., 47 lks. dist. with healed blaze.
A burned and dead Fir 23" dia., bears S.44½°E., 22 lks. dist. with healed blaze.
A burned and dead Fir 15" dia., bears S.39°W., 18 lks. dist. with healed blaze.
A burned and dead Fir 16" dia., bears N.34¼°W., 19 lks. dist. with healed blaze.
Set a 6 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21744-5)

The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 2" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd. from which the remains of the original bearing trees
A burned decayed fir stump, 17" dia., bears S.45°W., 38.3 ft., with a healed blaze. (Record, S.41°W.)
A burned decayed fir stump, 33" dia., bears N.87°W., 44.9 ft., no marks visible.
and the remains of bearing trees mkd. by Tillman in 1950
A decayed fir snag, 26" dia., bears N.60°E., 31.0 ft., with scribe marks 20S 8W 6 B and other illegible scribe marks visible on partially healed blaze.
A decayed fir snag, 20" dia., bears S.46¾°E., 14.5 ft., with illegible scribe marks visible on partially healed blaze. (Record, S.44¼°E.)

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir snag, 19" dia., bears S.34³/₄°W., 11.9 ft., with a healed blaze. (Record, S.39°W.)
A decayed fir snag, 14" dia., bears N.36¹/₄°W., 12.5 ft., with a healed blaze. (Record, N.34¹/₄°W.)
and new bearing trees
A fir, 8" dia., bears N.15°E., 15.8 ft., mkd. T20S R8W S36 BT.
A fir, 8" dia., bears S.42¹/₂°E., 13.1 ft., mkd. T21S R8W S1 BT.
A fir, 11" dia., bears S.63¹/₂°W., 23.0 ft., mkd. T21S R8W S2 BT.
A fir, 8" dia., bears N.53°W., 17.0 ft., mkd. T20S R8W S35 BT.
There is a steel fence post alongside the corner.

FD. as per rec. 8/2016 by Ron Rice, M172-31