

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 464)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Maple, 6" dia., bears N.20°W., 30 lks., mkd: ¼ S BT.
Fir, 7" dia., bears S.24°W., 10 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 292, Surveyed June/Oct. 1950 (DCSO records Vol. 27 Page(s) 11335-6)

Point for ¼ sec. cor. of secs. 35 & 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft long, 1" dia., 28" in the ground, with brass cap marked:

¼
S35|S36
1950

from which
A Fir, 12" dia., bears N.15°E., 21 lks. mkd: ¼ S36 BT.
A Fir, 16" dia., bears S.70°W., 22 lks., mkd: ¼ S35 BT.

BLM remonumentation of certain Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16718)

The ¼ sec. cor. of secs. 35 & 36, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground with brass cap (properly) mkd.

from which the remains of the BTs marked in 1950
A root hole, bears N.15°E., 21 lks., with a down & burned Fir alongside, 15" dia, with healed blaze.
A root hole, bears S.70°W., 22 lks., with a down & burned Fir alongside, 20" dia, with healed blaze.

and new BTs
A burned fir snag, 20" dia., bears S.89½°E., 49½ lks., mkd: ¼ S36 BT.
A burned fir snag, 19" dia., bears S.86½°W., 59½ lks., mkd: ¼ S35 BT.

Set a 5 ft. steel fence post alongside the iron post.

Ronald L Rice - Aug. 2016 - Oxbow Timber 1 LLC - M172-31

Found - GLO brass cap dated 1950
12"x6' D.Fir staub bears S.86½°W., 39.3' - no marks
Rec. 20" fir snag bearing S.89½°E., 49½ lks, Not fd
continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 14" D.Fir bears N.32°E., 20.5' - blazed, scribed ¼
S36 BT
9" D.Fir bears S.12°E., 5.0' - blazed, scribed X BT
14" D.Fir bears S.89°W., 30.6' - blazed, scribed ¼
S35 BT
14" D.Fir bears N.29°W., 26.2' - blazed, scribed X BT
Steel post adjacent to corner