

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Pages 464-5)

-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 25, 26, 35, & 36 mkd. T 20 S S 25 on NE, R 8 W S 36 on SE, S 35 on SW, S 26 on NW face, with 1 notch on E & S edges; from which  
    Fir, 16" dia., bears N.16°E., 40 lks. mkd: T20S R8W S25 BT  
    Fir, 18" dia., bears S.27°E., 19 lks. mkd: T20S R8W S36 BT  
    Fir, 21" dia. bears S.40°W., 100 lks. mkd: T20S R8W S35 BT  
    Fir, 27" dia. bears N.79°W., 100 lks. mkd: T20S R8W S26 BT

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO records Vol. 27 Page(s) 11336)

-----  
Point for the cor. of secs. 25, 26, 35, & 36 at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:  
                                  T20S R8W  
                                  S 26|S 25  
                                  S 35|S 36  
                                  1950

from which  
    A fir, 54" dia., bears N.78°E., 104 lks., mkd: T20S R8W S25 BT.  
    A hemlock, 8" dia., bears S.47°45'E., 84 lks., mkd: T20S R8W S36 BT.  
    A hemlock, 8" dia., bears S.65°45'W., 21 lks., mkd: T20S R8W S35 BT.  
    A fir, 54" dia., bears N.83½°W., 94 lks., mkd: T20S R8W S26 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16718)

-----  
The cor. of secs. 25, 26, 35, & 36, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap properly mkd.  
from which the remains of the BTs marked in 1950  
    A sawed & burned fir stump, 47" dia., bears N.78°E., 104 lks., no marks remaining. Rescribed T20S R8W S25 BT on new blaze.  
    A burned hemlock snag, 15" dia., bears S.47¾°E., 81 lks., with fragmentary scribe marks visible on partially healed blaze. (rec. 84 lks.) continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burned hemlock snag, 14" dia., bears S.65¼°W., 21 lks., with fragmentary scribe marks visible on partially healed blaze.

A burned fir snag, 50" dia., bears N.83½°W., 94 lks., with no marks remaining on burned blaze. Rescribed T20S R8W S26 BT on new blaze.

Set a 6 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21755)

-----  
The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2" dia. firmly set, 42" below the ground with brass cap (properly) mkd.

from which the remains of a BT mkd. by Tillman in 1950

A fir stump, 49" dia., bears N.83½°W., 62.0 ft., no marks visible.

and new bearing trees

A fir, 9" dia., bears N.47¼°E., 30.7 ft., mkd. T20S R8W S25 BT.

A fir, 9" dia., bears S.66°E., 21.9 ft mkd T20S R8W S36 BT

A fir, 8" dia., bears S.69°W., 14.1 ft mkd T20S R8W S35 BT

A fir, 9" dia., bears N.74¼°W., 13.5 ft., mkd. T20S R8W S26 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Ronald L. Rice, Ward NW Inc. - Jason Collier - Feb. 13, 2012 - C.S. File 65/76-16

-----  
Found - BLM brass cap, 1950, buried 42" below ground with the following accessories:

14" D.Fir bears N.47°E., 30.7' - healed face

10" D.Fir bears S.66°E., 21.9' - scribing visible

8" D.Fir snag bears S.69°W., 14.1' - scribing visible

10" D. Fir bears N.74°W., 13.5' - healed face

49" D.Fir stump bears N.83½°W., 62.0' - no marks visible

Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.

Compass Declination 16° East

Fd. as per M167-69 - Set 6 ft. steel post S.84°E., 2 ft. - by David Edwards, 1/2015 - M169-1

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23181-2)

-----  
The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set, with top 42 ins. below the surface of the ground, with a brass cap (properly) mkd. from which the remains of a BT mkd. by Tillman in 1950

A decayed fir stump, 41" dia., bears N.83½°W., 62.0 ft., with axe marks.

and the remains of the BTs mkd. by Graham in 2005

A fir, 14" dia., bears N.47¼°E., 29.9 ft., with a healed blaze and a Mag Nail at the base on the right side center. (Record, 30.7 ft.)

A fir, 9" dia., bears S.66°E., 21.9 ft., with scribe marks R8W S36 BT and other illegible scribe marks visible on partially healed blaze and a Mag Nail at the base on the right side center.

A fir snag, 8" dia., bears S.69°W., 14.1 ft., with scribe marks T20S R8W S35 BT visible on open blaze and a Mag Nail at the base on the right side center.

A fir, 10" dia., bears N.74¼°W., 13.5 ft., with a healed blaze and a Mag Nail at the base on the right side center.

and a new bearing tree

A fir, 9" dia., bears S.86¾°W., 64.8 ft., mkd. T20S R8W S35 BT.

An aluminum fence post is alongside the cor.

Ronald L Rice - Aug. 2016 - Oxbow Timber 1 LLC - M172-31

-----  
Found - GLO brass cap dated 1950 with the following accessories:

41" rotted D.Fir stump bears N.83½°W., 62.0' - axe marks visible

14" D.Fir bears N.47¼°E., 29.9' - healed face

9" D.Fir bears S.66°E., 21.9' - scribing visible

8" D.Fir snag bears S.69°W., 14.1' - scribing visible

10" D.Fir bears N.74¼°W., 13.5' - healed face

9" D.Fir bears S.86¾°W., 64.8' - scribing visible

Steel post adjacent to corner