

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 467)

-----  
Set post, 6" dia., 4 ft. long in mound of stone, 18" high, 5 ft. sq. at base, for cor. to secs. 13, 14, 23, & 24, marked T20S S13 on NE., R8W S24 on SE., S23 on SW., S14 on NW., with 3 notches on S & 1 on E edges. No witness trees.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12357)

-----  
Point for the cor. of secs. 13, 14, 23, & 24 proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 12" in the ground, to solid rock, & in a mound of stone, 4 ft. base, to top, with brass cap marked:

T20S	R8W
<u>S 14</u>	<u>S 13</u>
S 23	S 24
1954	

from which

- A fir, 25" dia. bears N.51°E. 81 lks. mkd: T20S R8W S13 BT
- A maple, 25" dia., bears S.45¼°E., 83 lks., mkd: T20S R8W S24 BT.
- A maple, 30" dia., bears S.73°W., 22 lks., mkd: T20S R8W S23 BT.
- A maple, 23" dia., bears N.27°W., 34 lks., mkd: T20S R8W S14 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16721)

-----  
The cor. of secs. 13, 14, 23, & 24, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.

from which the remains of the BTs marked in 1954

- A burned fir snag, 27" dia., bears N.51°E., 81 lks., with fragmentary scribe marks visible on partially healed & burned blaze.
- A burned maple snag, 30" dia., bears S.45¼°E., 83 lks., with scribe marks T20S R8W S24 BT visible on open & burned blaze.
- A burned maple snag, 37" dia., bears S.73°W., 22 lks., with scribe marks BT visible on partially healed & burned blaze.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A burned maple snag, 25" dia, bears N.27°W., 34 lks., with healed blaze.  
 Set a 6 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21756-7)

-----  
 The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2" dia., firmly set, projecting 22" above the ground, in a mound of stone, 4 ft. base, 15" high, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Tillman, et al., in 1953-54

A burned fir stump, 27" dia., bears N.52½°E., 53.5 ft., with a healed blaze. (Record, N.51°E.)

A maple clump growing around a root hole, bears N.27°W., 22.4 ft., no marks visible.

and new bearing trees

A fir, 17" dia., bears N.13½°E., 33.7 ft., mkd. T20S R8W S13 BT.

A fir, 11" dia., bears S.32°E., 38.8 ft., mkd. T20S R8W S24 BT.

A fir, 14" dia., bears S.60½°W., 56.4 ft., mkd. T20S R8W S23 BT.

A fir, 10" dia., bears N.86½°W., 46.5 ft., mkd. T20S R8W S14 BT.

Corner falls on a steep rocky slope with thin soil cover. Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Ron Rice - March 1, 2013 - C.S. File 65/78-18

-----  
 Condition Report

- Found - 1954 GLO brass cap with the following accessories:  
 A burned fir stump, 27" dia., bears N.52½°E., 53.5 ft., with a healed blaze. (Found same)  
 A maple clump growing around a root hole, bears N.27°W., 22.4 ft., no marks visible. (Found same)  
 A fir, 17" dia., bears N.13½°E., 33.7 ft., mkd. T20S R8W S13 BT. (Found 21", healed face)  
 A fir, 11" dia., bears S.32° E., 38.8 ft., mkd. T20S R8W S24 BT. (Found 14", healed face)  
 A fir, 14" dia., bears S.60½°W., 56.4 ft., mkd. T20S R8W S23 BT. (Found 16", healed face)  
 A fir, 10" dia., bears N.86½°W., 46.5 ft., mkd. T20S R8W S14 BT. (Found 10", healed face)

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - None  
Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.  
Declination 16° East

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23184)

-----  
The cor. of secs. 13, 14, 23, & 24, monumented with an iron post, 2" dia., firmly set, projecting 16" above the top of a mound of stone, 3 ft. base, 2½ ft. high, with a brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Tillman, et al. in 1953-54

A burned decayed fir stump, 20" dia., bears N.53¾°E., 52.3 ft., no marks visible. (Record, S.52½°E., 53.5 ft.)

A roothole, with a maple clump, bears N.27°W., 22.4 ft., no marks visible.

and the bearing trees mkd. by Graham in 2005

A fir, 25" dia., bears N.13½°E., 32.3 ft., with a healed blaze and a Mag Nail at the base on the right side center. (Record, 33.7 ft.)

A fir, 15" dia., bears S.32°E., 38.8 ft., with a healed blaze and a Mag Nail at the base on the right side center.

A fir, 16" dia., bears S.60½°W., 56.4 ft., with a healed blaze and a Mag Nail at the base on the right side center.

A fir, 8" dia., bears N.86½°W., 46.5 ft., with a healed blaze and a Mag Nail at the base on the right side center.

An aluminum fence post is alongside the cor.