

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Pages 467-8)

Set post, 6" dia., 4 ft. long, in mound of rocks, 18" high 5½ ft. sq. at base, for cor. to secs. 11, 12, 13, & 14 mkd. T 20S S 12 on NE, R 8W S 13 on SE, S 14 on SW, S 11 on NW face, with 4 notches on S & 1 on E edge. No witness trees.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12359)

Point for the cor. of secs. 11, 12, 13, & 14, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R8W
S 11 | S 12
S 14 | S 13
1954

from which

- A fir, 28" dia. bears N.47°E. 68 lks. mkd: T20S R8W S12 BT
- A fir, 36" dia., bears S.62½°E., 45 lks., mkd: T20S R8W S13 BT.
- A fir, 30" dia. bears S.22°W. 24 lks. mkd: T20S R8W S14 BT
- A fir, 32" dia., bears N.16¾°W., 73 lks., mkd: T20S R8W S11 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16721-2)

The cor. of secs. 11, 12, 13, & 14, monumented with an iron post, 2" dia., firmly set, projecting 14" above ground, with brass cap (properly) marked

from which the remains of the BTs marked in 1954

- A root hole bears N.47°E., 68 lks., with a down & burned fir alongside, 28" dia., no marks visible.
- A fir, 37" dia., bears S.60°E., 47 lks., no marks remaining on burned blaze. (Rec. S.62½°E., 45 lks.) Rescribed T20S R8W S13 BT.
- A fir, 30" dia., bears S.18°W., 24 lks., no marks remaining on burned blaze. (Rec. S.22°W.)
- A fir, 34" dia., bears N.13½°W., 73 lks., with burned blaze. (Rec. N.16¾°W.) Rescribed T20S R8W S11 BT.

and new BT

- A fir, 35" dia. bears N.54°E. 29 lks. mkd: T20S R8W S12 BT

cont.

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Ron Rice - March 1, 2013 - C.S. File 65/78-20

Found - 1954 GLO brass cap with the following accessories:
no 37" D.Fir snag bears S.60°E., 31.0' - burned face,
scribe marks
30" D.Fir snag bears S.18°W., 15.8' - no marks
34" D.Fir stump bears N.13½°W., 48.2' - burned face,
no scribing
35" D.Fir stump bears N.54°E., 19.1' - rotted face,
cruiser mark in bark
New - 8" D.Fir bears N.21°W., 11.2 ft. - blazed, scribed,
T20S R8W S11 BT
14" D.Fir bears N.38°E., 24.2 ft. - blazed, scribed,
T20S R8W S12 BT
15" D.Fir bears S.1°E., 24.6 ft. - blazed, scribed,
T20S R8W S13 BT
12" D.Fir bears S.26°W., 9.8 ft. - blazed, scribed,
T20S R8W S14 BT
Note - Corner has steel post adjacent to it. All BTs have
red painted bands and yellow tags.
Declination 16° East