

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 468)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 6" dia., bears N.22°W., 47 lks., mkd: ¼ S BT.
Fir, 7" dia., bears S.72°E., 50 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12360-1)

Point for the ¼ sec. cor. of secs. 11 & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 11|S 12
1954

A fir, 11" dia., bears S.54¼°E., 47 lks., mkd: ¼ S12 BT.
A fir, 10" dia., bears S.63½°W., 22 lks., mkd: ¼ S11 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16723)

The ¼ sec. cor. of secs. 11 & 12, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which remains of the BTs marked in 1954

A burned fir snag, 11" dia., bears S.54¼°E., 22 lks., with healed blaze (rec. 47 lks.) BT.

A burned fir snag, 14" dia., bears S.65°W., 47 lks., with healed blaze (rec. S.63½°W., 22 lks.)

and a new BT

A fir, 26" dia., bears S.71°E., 62 lks., mkd: ¼ S12 BT.

Set a 6 ft. steel fence post alongside the iron post.

Les Roberts - For: International Paper Co. - Dec. 1986 - M103-63 & CS 63/46-3(D)

Found - 1954 GLO brass cap correctly stamped, set firmly in the ground.

A 10" fir stump bears S.54°E., 14.5' (no marks) 1954
BT rec. S.54¼°E., 31.0'.

12" Fir stump bears S.65°W., 31.0' (no marks) 1954
BT rec. S.63½°W., 14.5'. continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

	21" fir bears S.70°E., 40.5' (scar vis.) 1967 BT rec. S.71°E., 40.9'
Set -	A 6" fir, bears N.9°W., 25.9' (scribed/painted red)
Note -	Set metal fence post, with survey attention sign wired to, beside brass cap. Painted all BTs red. Corner lies on top of ridge. Ridge bears NW & SE.