

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Pages 468-9)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 1, 2, 11, & 12, mkd. T 20S S 1 on NE, R 8W S 12 on SE, S 11 on SW, S 2 on NW face, with 5 notches on S & 1 on E edge; from which
Fir, 6" dia., bears N.22°E., 20 lks., mkd: T20S R8W S1 BT.
Fir, 8" dia., bears S.25°E., 27 lks. mkd: T20S R8W S12 BT.
Fir, 9" dia., bears S.40°W., 50 lks. mkd: T20S R8W S11 BT.
Fir, 4" dia., bears N.42°W., 55 lks., mkd: T20S R8W S2 BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12361)

Point for the cor. of secs. 1, 2, 11 & 12, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:
T20S R8W
S 2 | S 1
S 11 | S 12
1954

from which
A fir, 10" dia., bears N.48°E., 7 lks. mkd: T20S R8W S1 BT
A fir, 18" dia., bears S.52½°E., 39 lks., mkd: T20S R8W S12 BT.
A fir, 12" dia. bears S.20°W., 8 lks. mkd: T20S R8W S11 BT
A fir, 17" dia. bears N.50°W., 41 lks. mkd: T20S R8W S2 BT

Fd. ok, BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16723)

Fd. Ok by Les Roberts, Dec. 1986, M103-63 & CS 63/46-3(C)

David Edwards - For: Roseburg Resources - April 2019 - M175-39

Found - Brass cap
12" Fir snag bears N.47°E., 4.7'
34" Fir bears S.53°E., 26.8'
18" fir bears S.17°W., 5.3'
25" Fir bears N.50°W., 26.2'
All with healed blaze
Set - A 6' steel post 2' N.1°E.