

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T19-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 463-64)

Set post 6" dia., 4 ft. long, with marked stone 12" in ground for cor. to secs. 35, 36, 1 & 2, marked T19S S36 on NE.; R8W S1 on SE.; T20S S2 on SW.; S35 on NW. faces, with 5 notches on W. & 1 on E. edges; from which
Fir 12" dia., bears N.42°E., 21 lks. dist., mkd. T19S R8W S36 BT.
Fir 8" dia., bears S.41°E., 19 lks. dist. mkd. T20S R8W S1 BT.
Fir 8" dia., bears S.55°W., 47 lks. dist. mkd. T20S R8W S2 BT.
Fir 10" dia., bears N.77°W., 33 lks. dist. mkd. T19S R8W S35 BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 507)

At the sec.cor., where finding only the burnt end of the original post, I set a new post, 4½ ft. long, 4" sq., 24" in ground, mkd. T19S S36 on NE.; R8W S1 on SE.; T20S S2 on SW.; S35 on NW. faces, with 5 notches on W. and 1 notch on E. edges; from which the original bearing trees are found as described by Wright.

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12913-14)

The point for the sec. cor., at proportionate distance; there is no remaining evidence of the orig. corner.
Set an iron post 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:

T19S	R8W
S 35	S 36
S 2	S 1
T20S	
1952	

from which
A Fir 22" dia., bears N.52°E., 23 lks. dist. mkd. T19S R8W S36 BT.
Fir 12" dia., bears S.69½°E., 35 lks. dist. mkd. T20S R8W S1 BT.
A Fir 11" dia., bears S.68¼°W., 28 lks. dist. mkd. T20S R8W S2 BT. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T19-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Fir 15" dia., bears N.49½°W., 54 lks. dist. mkd. T19S R8W S35 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16715-16)

The Sec. Cor., monumented with an iron post 2" dia., firmly set, projecting 8" above ground, with brass cap mkd. in 1952, from which bearing trees mkd. in 1952

(Cont. Next Page)

A Fir 23" dia., bears N.57°E., 23 lks. dist., healed blaze. (Rec. N.52°E.)

A Fir 15" dia., bears S.69½°E., 38 lks. dist., healed blaze. (Rec. 35 lks.)

A Fir 15" dia., bears S.68¼°W., 28 lks. dist., healed blaze.

A Fir 20" dia., N.49½°W., 54 lks. dist., healed blaze.
Set a 6 ft. steel fence post alongside the iron post.

Fd. OK, Dec. 1986 by Skinner - M 103-6

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23179-80)

The cor. of secs. 1, 2, 35, 7 36, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with a brass cap(properly) mkd.

from which the remains of the BTs mkd. by Lytle & Norseth in 1952

A decayed fir snag, 23" dia., bears N.57°E., 15.2 ft., with a healed blaze.

A roothole bears S.69½°E., 25.1 ft., alongside of which is a decayed rootwad, no marks visible.

A decayed fir high stump, 17" dia., bears S.66¼°W., 18.5 ft., with a healed blaze & X at breast height. (Record, S.68¼°W.)

A decayed fir snag, 24" dia., bears N.49½°W., 33.7 ft., with a healed blaze. (Record, 35.6 ft.)

and new bearing trees

A fir, 6" dia., bears N.70°E., 31.7 ft., mkd. T19S R8W S36 BT.

A fir, 11" dia., bears S.83¾°E., 41.1 ft., mkd. T20S R8W S1 BT.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T19-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 6" dia., bears S.27¼°W., 16.2 ft., mkd. T20S R8W
S2 BT.

A fir, 6" dia., bears N.16½°W., 15.0 ft., mkd. T19S R8W
S35 BT.

Corner is located in an area of young second growth, with a red steel fence post with an International Paper property sign and a yellow steel fence post alongside the cor.