

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 467)

Set post, 4" dia., 4 ft. long, in mound of stone, 18" high, 3 ft. sq. at base, for qr. sec. cor. marked 1/4 S on N face. No witness trees.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12358)

Point for 1/4 sec. cor. of secs. 13 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:
1/4 S 13
S 24
1954

from which
A cedar, 33" dia., bears N.66°E., 76 lks., mkd: 1/4 S13 BT.
A cedar, 25" dia., bears S.36 1/4°E., 46 lks., mkd: 1/4 S24 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16721)

The 1/4 sec. cor. of secs. 13 & 24, monumented with an iron post, 1" dia. firmly set, projecting 4" above ground, & in a mound of stone, 1 ft. base, to top w/brass cap properly mkd from which
A cedar, 33" dia., bears N.66°E., 76 lks., with fragmentary scribe marks visible on partially healed & burned blaze. Rescribed 1/4 S13 BT on new blaze.
A cedar, 28" dia., bears S.36 1/4°E., 46 lks., with fragmentary scribe marks visible on partially healed & burned blaze. Rescribed 1/4 S24 BT on new blaze.

Ron Rice, NW Land Surveying - Sept. 2013 - C.S. File 65/80-21 & M167-70 (3/2014)

Found - 2 1/2" GLO brass cap, dated 1954, with the following accessories:
Cedar, 33" dia., bears N.66°E., 76 lks., with fragmentary scribe marks visible on partially healed & burned blaze. Rescribed 1/4 S 13 BT on new blaze. (Fd 33" Cedar stump, no scribing visible)

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New -	Cedar, 28" dia., bears S.36¼°E., 46 lks., with fragmentary scribe marks visible on partially healed & burned blaze. Rescribed ¼ S24 BT on new blaze. (Fd 31" Cedar stump, no scribing visible)
	19" D.Fir bears N.64°W., 4.2 ft - blazed, scribed ¼ S13 BT
	24" D.Fir bears N.81°E., 22.4 ft. - blazed, scribed ¼ S13 BT
	18" D.Fir bears S.74°E., 14.6 ft. - blazed, scribed ¼ S24 BT
	16" D.Fir bears S.70°W., 14.8 ft. - blazed, scribed ¼ S24 BT
Note -	Corner has steel post adjacent to it. All live BTs have red painted bands and yellow tags. Compass Declination 16° East