



PRIMARY CORNER DESCRIPTION 1/4 Secs. 12 & 13

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A stump hole, bears N.9°E., 52 lks.  
A stump hole, bears S.41°E., 33 lks.  
and the remains of the BTs marked in 1960  
A root hole, bears N.47°E., 34 lks., with a down cedar alongside, 8" dia., no marks visible.  
A root hole, bears S.44°E., 88 lks., with a down cedar alongside, 14" dia., with fragmentary scribe marks visible on open & burned blaze.  
and new BTs  
A fir stump, 36" dia. bears S.10°W., 56 lks. mkd: ¼ S13 BT  
A fir snag, 65" dia., bears N.23°W., 48 lks. mkd: ¼ S12 BT

---

Les Roberts - For: International Paper Co. - Dec. 1986 - M103-63 & CS 63/46-3(E)  
-----  
Found - 1954 GLO brass cap correctly stamped.  
Root hole bears N.47°E., 22.5' 1960 BT rec. N.47°E., 22.4'  
Root hole bears S.44°E., 58.0' 1960 BT rec. S.44°E., 58.1'  
26" fir stump bears S.11°W., 36.8' (Scribe visible) 1967 BT, rec. S.10°W., 37.0'.  
New - 6" Fir, bears S.15°E., 18.8' (scribed/painted red)  
12" Fir, bears N.46°E., 8.6' (scribed/painted red)  
Note - Set alum. fence post with survey attention sign, wired to beside brass cap. Painted all BTs red. Corner lies on spur ridge sloping East.

---

Ron Rice - For: Oxbow Timber 1 LLC - Jan. 2014 - C.S. File 65/81-3 & M167-67 (3/2014)  
-----  
Found - 2½" GLO brass cap dated 1954 with the following accessories:  
30" D.Fir stump bears S.11°W., 36.8', scribing visible.  
13" D.Fir bears S.15°E., 18.8', healed face  
22" D.Fir bears N.46°E 8.6', healed face  
New BT - 11" D.Fir bears S.88°W 9.9', blazed scribed ¼ S13 BT  
Aluminum post adjacent to corner

---

2