

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 469)  
-----  
Set post, 4" dia., 4 ft. long, in mound of stone, 18" high, 3 ft. sq. at base, for qr. sec. cor., marked ¼ S on N face. No witness trees.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12361-2)  
-----  
Point for the ¼ sec. cor. of secs. 1 & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 12" in the ground to solid rock, and in a mound of stone, 3 ft. base, 2 ft. high with brass cap marked: ¼  $\frac{S \ 1}{S \ 12}$   
1954  
from which  
A fir, 10" dia., bears N.37°E., 21 lks., mkd: ¼ S1 BT.  
A fir, 12" dia., bears S.60¼°W., 21 lks., mkd: ¼ S12 BT.

Fd. ok, BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16723-4)