

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 36, T19-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 464)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for gr. sec. cor. marked $\frac{1}{4}$ S on N. face; from which
Maple 6" dia., bears N.20°W., 30 lks. dist. mkd. $\frac{1}{4}$ S BT.
Fir 7" dia., bears S.24°W., 10 lks. dist. mkd. $\frac{1}{4}$ S BT.

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12913)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, with brass cap mkd: $\frac{1}{4}$ $\frac{S\ 36}{S\ 1}$
1952

from which
A Fir 32" dia., bears N.49°E., 80 lks. dist. mkd. $\frac{1}{4}$ S36 BT.
A Fir 12" dia., bears S.26 $\frac{1}{2}$ °W., 67 lks. dist. mkd. $\frac{1}{4}$ S1 BT.

Survey by Donald Peel - For: International Paper Co. - Aug. 13, 1982 - M 92-77

Found - 1" I.P. with GLO brass cap, 1952.
44" Fir N.49°E., 53.2 ft.
15" Fir S.26 $\frac{1}{2}$ °W., 44.0 ft., blown down.
New BT - 26" Fir S.36°E., 55.4 ft.