

PRIMARY CORNER DESCRIPTION C.C. for Secs. 30 & 31, T20-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 620)

Set a post at point of intersection (18.20 chs. N.1°E. of cor. to secs. 25 & 36) 4 ft. long, 4" sq., 24" in the ground for closing cor. to secs. 30 & 31, marked CC T20S R7W on E.; S30 on N. face; S31 on S. face, with 5 notches on N. & 1 notch on S. faces; from which

- A Fir 12" dia., bears N.20°E., 18 lks. dist. mkd. T20S R7W S30 BT.
- A Fir 24" dia., bears S.57°E., 25 lks. dist. mkd. T20S R7W S31 BT.
- A Fir 18" dia., bears N.82°W., 32 lks. dist. mkd. T20S R7W CC S30 & 31 BT.
- A sandstone 20x20 ins., in place marked WC, bears N.80°W., 6 lks. dist.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #292, Surveyed June/Oct. 1950 - (DCSO records Vol. 27 Page(s) 11331)

The closing cor., monumented with a wooden post, 3" sq., 4 ft. above ground, firmly set, marked T20S R7W S30 & 31 with a lumber crayon, from which

- A Fir 40" dia., bears N.3¼°E., 226 lks. dist., with the scribe marks T20S R7W visible on the opened blaze. (There is no record of this bearing tree, but a count of annual growth rings dates the blaze at 1891.)
- A stump hole, from which a Fir, 48" dia., has slid down the hill, bears N.20°E., 18 lks. dist., with the blaze covered by earth and rocks. (agrees with Todd's rec.)
- A Fir 32" dia., bears S.33°E., 25 lks. dist., plainly blazed and healed. (Rec. brg. S.57°E.)
- A dead Fir 18" dia., bears N.85°W., 32 lks. dist., with partial scribe marks visible on the partly opened blaze. (Rec. brg. N.82°W.)
- A sandstone in place, 20x20x4 ins. above ground, bears N.80°W., 6 lks. dist., with the chiseled marks WC plainly visible. (agrees with Todd's rec.)

BLM Resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #'s 350 & 622, Surveyed Oct. 1966/May 1967 - (DCSO records Vol. 34 Page(s) 14143-44)

True point for the closing cor. of secs. 30 & 31.
Set an iron post 24" long, 1" dia., 5" in drill hole in solid sandstone 12" below the surface of the ground, with brass cap marked:
(Cont. Next Page)

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 700218

PRIMARY CORNER DESCRIPTION C.C. for Secs. 30 & 31, T20-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 20 S	T 20 S
R 8 W	S 30 CC
S 25	S 31
	R 7 W

1966

Deposit a quart jar at the base and set a steel fence post alongside the iron post.

From this point, the original closing cor. bears S.89°34'W., 0.015 chs. dist., determined at record bearing and distance from the remaining original cor. accessories:

A burned Fir, 40" dia., bears S.33°E., 25 lks. dist. mkd. with a healed blaze.

A burned Fir snag, 15" dia., bears N.85°W., 32 lks. dist. with burned out blaze, no scribe marks visible.

A sandstone in place 20x20x4 ins., above ground, bears N.80°W., 6 lks. dist., with chisel marks WC plainly visible.

and a bearing tree reported by Tillman in 1950:

A burned Fir 48" dia., bears N.3¼°E., 233½ lks. dist. mkd. with a burned out blaze, no scribe marks visible. (Rec. dist. 226 lks.)

Ronald Rice - For: Oxbow Timber 1 LLC - Sept. 2015 - M170-15A&B

Found - GLO brass cap dated 1966
40" rotted D.Fir stump bears S.33°E., 16.5' no marks
15" rotted D.Fir stump bears N.85°W., 21.1' no marks
Sandstone 20x20x4" above ground bears N.80°W., 4.0'
- WC chisel makes.

New - 34" D.Fir snag bears N.3¼°E., 154.1' - no marks
19" D.Fir bears S.86°E., 30.5' - blazed, scribed
T20S R7W S31 CC BT
14" D.Fir bears S.46°W., 5.2' - blazed, scribed X BT
Steel post adjacent to corner.