

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____


GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 456)

Set post 6" dia., 4 ft. long, with marked stone 12" in ground for qr. sec.cor., marked ¼ S on W. face; from which
Fir 20" dia., bears S.87°W., 31 lks. dist. mkd. ¼ S BT.
Fir 20" dia., bears S.72°E., 21 lks. dist. mkd. ¼ S BT.

Fd. OK and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 577-78)

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #292, Surveyed June/Oct. 1950 - (DCSO records Vol. 27 Page(s) 11331-32)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:



from which
A Fir 42" dia., bears S.85½°W., 62 lks. dist., mkd. ¼ S25 BT.
A Fir 50" dia., bears N.70½°W., 136 lks. dist. mkd. ¼ S25 BT.

BLM Resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #'s 350 & 622, Surveyed Oct. 1966/May 1967 - (DCSO records Vol. 34 Page(s) 14137-38)

The ¼ sec. cor., monumented with an iron post 1" dia., protruding 14" above the ground, firmly set, with brass cap mkd. in 1950,
from which bearing trees mkd. by Tillman in 1950
A sawed and burned Fir stump 45" dia., bears S.85½°W., 62 lks. dist., with burned out blaze, no scribe marks visible.
A sawed and burned Fir stump 44" dia., bears N.75½°W., 136 lks. dist., with scribe marks BT visible on remaining portion of opened blaze. (Rec. brg. N.70½°W.)
No live bearing trees available within limits in sec. 25.
Set a steel fence post alongside the iron post.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Ronald Rice - For: Oxbow Timber 1 LLC - Sept. 2015 - M170-15A&B

Found -	GLO brass cap dated 1950
	40" D.Fir stump bears S.85½°W., 40.9' - no marks
	39" D.Fir stump bears N.75½°W., 89.8' - no marks
New -	13" D.Fir bears N.48°E., 3.2' - blazed, scribed X BT
	9" D.Fir bears N.52°W., 10.5' - blazed, scribed X BT