

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Con. #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 457)

-----  
Set post 4" dia., 4 ft. long, with marked stone 12" in ground for qr. sec. cor., marked ¼ S on W. face; from which  
Cedar 14" dia., bears S.53°W., 12 lks. dist., mkd. ¼ S BT.  
Cedar 20" dia., bears N.62°E., 24 lks. dist., mkd. ¼ S BT.

Fd. OK and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 578)

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12341)

-----  
The ¼ sec. cor. of sec. 24, determined at record bearing and distance from the original bearing trees:

A Cedar 37" dia., bears N.62°E., 24 lks. dist., with marks ¼ S BT uncovered.

A Cedar 21" dia., bears S.53°W., 12 lks. dist., with portions of scribe marks uncovered.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: ¼ S 24\*  
1954

from which a new bearing tree:

A Fir 62" dia., bears N.7°W., 74 lks. dist. mkd. ¼ S24 BT  
Cor. falls on top of ascent on W. slope.

BLM Resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #'s 350 & 622, Surveyed Oct. 1966/May 1967 - (DCSO records Vol. 34 Page(s) 14139-40)

-----  
The ¼ sec. cor., monumented with an iron post 1" dia., protruding 12" above the ground, firmly set, with brass cap mkd. in 1954,

from which the original bearing tree mkd. by Wright:

A burned Cedar 36" dia., bears N.62°E., 24 lks. dist., with burned out blaze, no scribe marks visible.

A burned Cedar 22" dia., bears S.53°W., 12 lks. dist. with burned out blaze, no scribe marks visible.

and a bearing tree mkd. by Tillman in 1954:

A burned Fir 62" dia., bears N.7°W., 74 lks. dist., with illegible scribe marks visible on partially healed and burned blaze.

Set a steel fence post alongside the iron post.

cont.

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21749)

-----  
The ¼ sec. cor. of sec. 24 only, monumented with an iron post, 1" dia., firmly set, projecting 12 ins. above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A decayed cedar stump, 39" dia., bears N.62°E., 15.8 ft., with no marks visible on partially healed blaze.

A root hole with uprooted burned cedar log, 20" dia., bears S.53°W., 7.9 ft., no marks visible.

and a bearing tree mkd. by Tillman, et al., in 1953-54

A fir snag, 56" dia., bears N.7°W., 48.8 ft., with scribe marks ¼ visible on open blaze.

and new bearing trees

A fir, 8" dia., bears N.78°W., 7.7 ft., mkd. X BT.

A fir, 16" dia., bears N.9½°W., 33.6 ft., mkd. ¼ S24 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

-----  
Ron Rice, NW Land Surveying - Oct. 2013 - C.S. File 65/80-23

Condition report only

Found - 2½" GLO brass cap, dated 1954, with the following accessories:

Decayed cedar stump, 39" dia., bears N.62°E., 15.8 ft., with no marks visible on partially healed blaze. (Found same)

Root hole with uprooted burned cedar log, 20" dia., bears S.53°W., 7.9 ft. no marks visible (Fd same)

Fir snag, 56" dia., bears N.7°W., 48.8 ft., with scribe marks ¼ visible on open blaze. (Fd same)

Fir, 8" dia., bears N.78°W., 7.7 ft., mkd. X BT. (Found 10" fir with healed face)

Fir, 16" dia. bears N.9½°W., 33.6 ft., mkd. ¼ S24 BT. (Fd 18" fir with healed face)

(Found 16" D.Fir bearing N.42°E 20.3 ft. with healed face. Appears to be 2005 BLM unrecorded BT)

Note - Corner has steel post adjacent to it. All live BTs have red painted bands and yellow tags.

Compass Declination 16° East