

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 457)

-----  
Set post 6" dia., 4 ft. long, with marked stone 12" in ground for cor. to secs. 13 & 24, marked T20S R7W S19 on E.; T20S R8W S24 CC on SW.; S13 CC on NW. faces, with 3 notches on N. & S. edges; from which

Maple 12" dia., bears N.62°E., 41 lks. dist. mkd. T20S R7W S19 BT.

Fir 24" dia., bears S.74°W., 33 lks. dist. mkd. T20S R8W S24 BT.

Fir 18" dia., bears N.60°W., 58 lks. dist. mkd. T20S R8W S13 BT.

Fd. OK, and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 578-79)

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12342)

-----  
The cor. of secs. 13 & 24, located on blazed line, at record bearing from the remaining original bearing trees:

A Maple 20" dia., bears N.62°E., 39 lks. dist. mkd. with a healed blaze. (Rec. dist., 41 lks.)

A Fir 44" dia., bears S.74°W., 31 lks. dist., with no marks visible on opened blaze. (Rec. dist., 33 lks.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S*	T 20 S
S 13 *	R 7 W
S 24 *	S 19
R 8 W*	
1954	

from which a new bearing tree:

A Fir 48" dia., bears N.38 3/4°W., 65 lks. dist., mkd. T20S R8W S13 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only, (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16699-700)

-----  
The Sec. cor., monumented with an iron post, 2' dia., firmly set, projecting 6" above ground, and in a mound of stone, 1 ft. base, to top, with brass cap mkd. in 1954, from which the remains of the original bearing trees:

A Maple stump 24" dia., bears N.70°E., 36 lks. dist., no marks remaining on burned blaze. (Rec. N.62°E., 39 lks.)

A burned Fir stump 30" dia., bears S.65°W., 31 lks. dist., no marks remaining on burned blaze. (Rec. S.74°W.) and the remains of the bearing tree mkd. in 1954:

A decayed Fir stump 36" dia., bears N.41°W., 63 lks. dist., no marks remaining.

from which a new bearing tree and a bearing object:

A sawed Fir stump 33" dia., bears N.27°W., 93 lks. dist. mkd. T20S R8W S13 BT.

A sandstone outcrop, 3x6x3 ft., above ground, bears S.19½°W., 62½ lks. dist., mkd. X on face.

Ron Rice, NW Land Surveying - Oct. 2013 - C.S. File 65/80-24 & M167-70 (3/2014)

-----  
Found - 2½" GLO brass cap, dated 1954, with the following accessories:

Maple stump 24" dia., bears N.70°E., 36 lks., no marks remaining on burned blaze. (Missing)

Burned Fir stump 30" dia., bears S.65°W., 31 lks., no marks remaining on burned blaze. (Found same)

Decayed Fir stump 36" dia., bears N.41°W., 63 lks., no marks remaining. (Missing)

Sawed Fir stump 33" dia., bears N.27°W., 93 lks. mkd. T20S R8W S13 BT. (Found same)

Sandstone outcrop 3x6x3 ft. above ground bears S.19½°W., 62½ lks. mkd. X (Not recovered)

New - 19" D.Fir bears N.22°W., 17.3 ft. - blazed, scribed T20S R8W S13 BT

19" D.Fir bears S.68°W., 16.6 ft. - blazed, scribed T20S R8W S24 BT

Note - Corner has steel post adjacent to it. All live BTs have red painted bands and yellow tags.  
Compass Declination 16° East