

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 625)

(At a point 18.40 chs. N.1°E. of the old cor. to secs. 13 & 24)

I set a sandstone, 18x12x12 ins., 12" in the ground for closing cor. to secs. 18 & 19, marked CC with 3 notches on N. & S. faces; from which

A Fir 36" dia., bears N.24°E., 5 lks. dist. mkd. T20S R7W S18 BT.

A Fir 24" dia., bears S.79°E., 39 lks. dist. mkd. T20S R7W S19 BT.

A Maple 16" dia., bears S.37°W., 10 lks. dist. mkd. T20S R7W CC S18 & 19 BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12342-43)

The closing cor., determined at record bearing and distance from the remaining original bearing tree:

A turned out Fir 36" dia., bears S.79°E., 39 lks. dist., marked with a healed blaze.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S		T 20 S	
S 13		S 18	CC
		S 19	
R 8 W		R 7 W	
		1954	

from which new bearing trees:

A Fir 52" dia., bears N.58½°E., 120 lks. dist. mkd. T20S R7W S18 CC BT.

A Maple 14" dia., bears S.87°E., 84 lks. dist. mkd. T20S R7W S19 CC BT.

Corner falls on top of ascent on W. slope.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16700)

The closing cor. of secs. 18 & 19, on the W. bdy. of T20S R7W., monumented with an iron post 2" dia., firmly set, projecting 3" above ground with brass cap mkd. in 1954, from which the remains of the bearing trees mkd. in 1954:

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only, T20-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir snag, 52" dia., bears N.58½°E., 120 lks. dist., with burned blaze. Rescribed T20S R7W S18 BT on new blaze.
A burned Maple stump, size indeterminate, bears S.87°E., 84 lks. dist., no marks remaining on burned blaze.

Ron Rice, NW Land Surveying - Nov. 2013 - C.S. File 65/82-10 & M167-67 (3/2014)

Found - 2½" GLO brass cap, dated 1954, with the following accessories:
 Fir snag, 52"dia., bears N.58½°E., 120 lks., with burned blaze. Rescribed T20S R7W S18 BT on new blaze. (Fd 52" D.Fir stump, no marks)
 Burned Maple stump, size indeterminate, bears S,87°E., 84 lks., no marks remaining on burned blaze. (Not searched for)
New - 13" D.Fir bears N.52¾°W., 13.0 ft. - blazed, scribed X BT
 10" D.Fir bears N.28¼°E., 4.3 ft. - blazed, scribed T20S R7W S18 CC BT
 17" D.Fir bears S.25¼°E., 28.2 ft. - blazed, scribed T20S R7W S19 CC BT
Note - Corner has steel post adjacent to it. All live BTs have red painted bands and yellow tags.
 Compass Declination 16° East

Robert Cook - For: Roseburg Forest Products - July 2019 - M175-71

Found - 1954 GLO brass cap up 6" with steel post riser.
 13" D.Fir N.53°W., 13.0 ft.
 10" D.Fir N 28°E 4.3 ft.
 18" D.Fir S 25°E 28.2 ft.
All BT's painted, tagged and healed up.