

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, (East)

Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 458)

-----  
Set post 6" dia., 4 ft. long, with marked stone, 12" in ground for cor. to secs. 12 & 13, marked T20S R7W S18 on E.; T20S R8W S13 on SW.; S12 on NW. faces, with 2 notches on N. & 4 on S. edges; from which  
Cedar 45" dia., bears N.25°W., 12 lks. dist., mkd. T20S R8W S12 BT.  
Fir 40" dia., bears S.85°E., 25 lks. dist. mkd. T20S R7W S18 BT.  
Maple 28" dia., bears S.61°W., 17 lks. dist. mkd. T20S R8W S13 BT.

Cor. Fd. OK and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 579)

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12344)

-----  
The sec. cor., determined at record distances from the remaining original bearing trees:

- A Fir 60" dia., bears S.80°E., 25 lks. dist. with bark scribed marks BT S T remaining. (Rec. brg. S.85°E.)
- A Cedar 60" dia., bears N.35°W., 12 lks. dist., with no marks visible on decayed blaze. (Rec. brg. N.25°W.) I mark T20S R8W S12 BT in center of tree and below old blaze.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S*	T 20 S
S 12*	R 7 W
S 13*	S 18
R 8 W*	
1954	

from which a new bearing tree

- A Cedar 23" dia., bears S.86 3/4°W., 91 lks. dist., mkd. T20S R8W S13 BT. Bearing tree is in a branch, 2 lks. wide, course S.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, (East)

Alias	Description

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16701)

-----  
The sec. cor., monumented with an iron post, 2" dia., firmly set, projecting 3" above ground, with brass cap mkd. in 1954, from which the remains of the original bearing trees:

A Fir stump 60" dia., bears S.80°E., 25 lks. dist., no marks remaining in burned blaze.

A burned and dead Cedar 60" dia., bears N.35°W., 16 lks. dist. no marks remaining on burned blaze. (Rec. 12 lks.) Rescribed "T20S R8W S12 BT" on new blaze.

and the remains of the bearing tree mkd. in 1954:

A root hole, bears S.86 3/4°W., 89 lks. dist., with a down Cedar stump alongside, 23" dia., with scribe marks T20S R8W S13 BT visible on open blaze. (Rec. 91 lks.)

-----  
BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21750-1)

-----  
The cor. of secs. 12 and 13 only, monumented with an iron post, 2" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A burned decayed fir stump, 58" dia., bears S.80°E., 16.5 ft., with no scribe marks visible on decayed blaze.

A burned decayed cedar stump, 58" dia., bears N.35°W., 10.6 ft., with scribe mark B visible on open blaze. (Record, 7.9 ft.)

and new bearing trees

A fir, 16" dia., bears S.20½°W., 33.7 ft., mkd. T20S R8W S13 BT.

A fir, 22" dia., bears N.58½°W., 34.8 ft., mkd. T20S R8W S12 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

-----  
Ron Rice, NW Land Surveying - Nov. 2013 - C.S. File 65/82-12

-----  
Condition report only

Found - 2½" GLO brass cap, dated 1954, with the following accessories:

Burned decayed fir stump, 58" dia., bears S.80°E., 16.5 ft., with no scribe marks visible on decayed blaze. (Found same)

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, (East)

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Burned decayed cedar stump, 58" dia., bears N.35°W., 10.6 ft., with scribe mark B visible on open blaze. (Found same)  
Fir, 16" dia., bears S.20½°W., 33.7 ft., mkd. T20S R8W S13 BT. (Found 18" D. Fir with healed face)  
Fir, 22" dia., bears N.58½°W., 34.8 ft., mkd. T20S R8W S12 BT. (Found 25" D. Fir with healed face)  
Note - Corner has steel post adjacent to it. All live BTs have red painted bands and yellow tags.  
Declination 16° East.