

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 458-59)


Set post 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor., marked ¼ S on W. face; from which
Fir 12" dia., bears S.65°E., 13 lks. dist. mkd. ¼ S BT.
A Fir 40" dia., bears S.52°W., 7 lks. dist. mkd. ¼ S BT.

Cor. Fd. OK, and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 580)

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12345)

The ¼ sec. cor., determined at record bearing from the original bearing trees:
A Fir 20" dia., bears S.65°E., 15 lks. dist., with marks BT remaining on bark. (Rec. dist., 13 lks.)
A Fir 50" dia., bears S.52°W., 10 lks. dist., with marks BT ¼ S remaining on bark. (Rec. dist., 7 lks.)

At the corner point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:



from which a new bearing tree:
A Fir 60" dia., bears N.51½°W., 70 lks. dist., mkd. ¼ S12 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16701)

The ¼ sec. cor., monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap mkd. in 1954,
from which the original bearing trees:
A Fir 20" dia., bears S.65°E., 15 lks. dist., no marks remaining on decayed blaze.
A Fir 60" dia., bears S.52°W., 10 lks. dist., with healed blaze.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and a bearing tree mkd. in 1954:
A Fir 50" dia., bears N.51½°W., 70 lks. dist., with healed blaze. Rescribed "¼ S12 BT" on new blaze.

Survey by Les Roberts - For: International Paper Co. - Dec. 1986 - M 103-63 &CS 63/46-3(F)

Found - A 1954 GLO brass cap bent to the West, properly stamped.
A 16" Fir stump bears S.63°E., 10.2 ft., scar visible, 1884 BT. (Rec. S.65°E., 8.6 ft.)
54" Fir stump bears S.52°W., 6.2 ft., no marks, 1954 BT. (Rec. N.52°W., 4.6 ft.)
44" Fir stump bears N.51°W., 46.4 ft., scribe visible, 1954 BT. (Rec. N.51½°W., 46.2 ft.)
New BT - 8" Fir bears N.14°W., 10.0 ft., scribed, painted red.
R.R. spike in top of 54" Fir stump. Stump bears S.3°W., 5.3 ft. from corner.
Set metal fence post, with survey attention sign wired to, beside cap. Painted all BTs red.
Corner lies on West slope about 60 ft. East of a small draw.

Ron Rice - Feb. 28, 2013 - C.S. File 65/78-21

Found - A 1954 GLO brass cap bent to the West, properly stamped. (Straightened pipe)
16" Fir stump bears S.63°E., 10.2 ft., scar visible, 1884 BT. (Rotted face)
54" Fir stump bears S.52°W., 6.2 ft., no marks, 1954 BT. (Found RR spike in top at 6.2 ft.)
44" Fir stump bears N.51°W., 46.4 ft scribe visible, 1954 BT. (Same condition)
8" Fir bears N.14°W., 10.0 ft. scribed, painted red. (Fd 17" D.Fir with healed face)
RR spike in top of 54" Fir stump. Stump bears S.3°W., 5.3 ft. from corner. (Not fd)
New - 16" D.Fir bears S.12°E., 16.8 ft. blazed, scribed, X BT
21" D.Fir bears N.66°E., 13.0 ft. blazed, scribed, X BT
Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.
Declination 16° East