

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 459)

-----  
Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for gr. sec. cor., marked ¼ S on W. face; from which  
Fir 8" dia., bears S.68°E., 12 lks. dist. mkd. ¼ S BT.  
Fir 10" dia., bears S.63°W., 12 lks. dist. mkd. ¼ S BT.

Cor. Fd. OK, and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 581)

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12347)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 3 ft. long, 1" dia., 20" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:  
¼ S 1  
1954

from which  
A Fir 10" dia., bears N.19°W., 24 lks. dist., mkd. ¼ S1 BT  
A Fir 10" dia., bears S.47°W., 31 lks. dist., mkd. ¼ S1 BT

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16702)

-----  
The ¼ sec. cor., monumented with an iron post 1" dia., firmly set, projecting 10" above ground and in a mound of stone, 3 ft. base, to top, with brass cap mkd. in 1954, from which the remains of the bearing trees mkd. in 1954:  
A burned and dead Fir 15" dia., bears S.51°W., 31 lks. dist., with healed blaze. (Rec. S.47°W.)  
A Fir 15" dia., N.19°W., 24 lks. dist., with healed blaze.  
and a tree of which I have no record:  
A burned and dead Fir 15" dia., bears N.38½°E., 19 lks. dist., with healed blaze.  
and new bearing trees:  
A Fir 12" dia., bears S.29°W., 156 lks. dist. "¼ S1 BT"  
A Fir 18" dia., bears N.13°W., 83 lks. dist. "¼ S1 BT"

(Cont. Next Page)

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16090)

-----  
The ¼ sec. cor., monumented with an iron post, 1" dia., firmly set, projecting 7" above ground, with brass cap mkd. in 1954,

from which the remains of bearing trees mkd. by Tillman, etal  
A sawed Fir stump 12" dia., bears S.51°W., 31 lks. dist., with healed blaze.

A sawed Fir stump 15" dia., bears N.19°W., 24 lks. dist., with healed blaze.

and a bearing tree described by Glenn, etal

A sawed Fir stump 16" dia., bears N.38½°E., 19 lks. dist., with healed blaze.

and the only remaining bearing tree mkd. by Glen, etal

A Fir 15" dia., bears S.29°W., 156 lks. dist., with healed blaze.

No suitable trees available within limits.

Set a 5 ft. steel fence post alongside.