

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #260 dated April 17, 1877 (DCSO records Vol. 1 Page(s) 191)

-----  
Set a Cedar post as corner for secs. 31, 36, 6 and 1, T20 and 21 S., Rs. 9 and 10; from which  
A Fir 24" dia., bears N.32¼°W., 65 lks. dist.  
A Maple 14" dia., bears N.64°E., 74 lks. dist.  
A Maple 12" dia., bears S.12½°E., 49 lks. dist.  
A Fir 36" dia., bears S.33¼°W., 44 lks. dist.

Fd. and tied in GL0 survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 1 Pg. 364 and Vol. 2 Pg. 911)

GL0 resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (Group #36) (surveyed 1919) - (DCSO records Vol. 1 Page(s) 260-61) and (Dup. Pg. 1066)

-----  
Intersect point for the cor. of Tps. 20 S., Rs. 9 and 10 W., located by reference to the old bearing trees, which are marked as described by the surveyor general. At the exact cor. point, SET an iron post 3 ft. long, 3" dia., 24" in the ground, for cor. of Tps. 20 S., Rs. 9 and 10 W., with brass cap marked:  
T20S  
R10W | R9W  
S36 | S31  
1919

from which  
A Maple 14" dia., bears N.64°E., 74 lks. dist. mkd. T20S R9W S31 BT. (Old BT)  
A Fir 24" dia., bears N.32°W., 65 lks. dist. mkd. T20S R10W S36 BT. (Old BT)

H.T. Lewis, Engineer #722, Nov. 10, 1939 - (Old Cor. renewal Vol. 1 Pg. 6)

-----  
At this corner, I found the original Pipe set for this cor. of which was mkd. in 1919. This pipe has been upset by a falling tree but as the NW witness tree was in place, I RESET the pipe, from which  
A Cedar 8" dia., bears N.65°E., 17 ft. mkd. T20S R9W S31 BT CS 722.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11663-64)

-----  
The cor. of Tps. 20 S., Rs. 9 and 10., on the N. bdy. of sec. 1, T21S R10W., which is monumented with an iron post, 3 ft. long, 3" dia., firmly set, 24" in the ground and in a scattered mound of stone, with brass cap mkd. in 1918, from which

A Fir snag 30" dia., bears N.32°W., 63 lks. dist., with illegible scribe marks visible on decayed blaze. (Rec. distance, 65 lks.)

The iron post being rusted nearly through, I replace it with an iron post 3 ft. long, 3" dia., 24" in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked;

T 20 S  
R 10 W | R 9 W  
S 36 | S 31  
-----  
T 21 S R 10 W S 1  
1951

from which new bearing trees:

A Cedar 16" dia., bears N.66½°E., 26 lks. dist. mkd. T20S R9W S31 BT.

A Cedar 16" dia., bears N.57°W., 52 lks. dist. mkd. T20S R10W S36 BT.

Deposit the old iron post at the base of the new iron post.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 30, 1969 - C.S. File 53/66-17

-----  
Found - GLO brass cap, properly marked in 1951.  
16" now 17" Cedar N.66½°E., 17.2 ft., shows good scar.

16" now 19" Cedar N.57°W., 34.3 ft., scribe visible "S".

New BT - 24" Maple S.24°E., 29.8 ft. mkd. "T21S R10W S1 CS BT"

Also tagged other bearing trees.

Fd. OK, Sept. 1983 by R. Stuntzner - M 95-12

Jerry Estabrook - For: Roseburg Resources - 1/2022 - M180-48

-----  
FOUND - A 3" iron pipe with 3½" brass cap (properly) marked  
Set steel post alongside.

A 42" Cedar with healed face and tag bears N.66°30'E., 17.16'.

Continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 41" Cedar with healed face and tag bears N.57°W.,  
34.32'  
New BTs- A 13" Fir, face scribed "X BT" with X-chop and tag  
bears S.70°E., 69.5' to a spike at side center.  
An 18" Maple, bark scribed "X BT with X-chop and tag  
bears S.42°E., 32.8' to a spike at side center.  
Lat and Long per GARMIN ETREX hand held GPS:  
N: 43°46'57.7" W: 123°49'47.5"