

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & 36, T20-10

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO Survey by Wm. Thiel under Contract #260 dated April 17, 1877 - (DCSO records Vol. 1 Page(s) 191)

Set a Cedar post for ¼ sec. corner, from which
A Fir 40" dia., bears S.86¼°E., 60 lks. dist.
An Alder 15" dia., bears S.26¼°W., 44 lks. dist.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11672)

The ¼ sec. cor. of secs. 31 & 36, monumented with an unmarked sandstone, 18x18x16 ins., firmly set 12" in the ground from which the remaining original bearing tree:

A Fir 54" dia., bears S.86¼°E., 60 lks. dist., plainly blazed and healed.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: ¼

S 36 S 31
1951

from which a new bearing tree:

A Cedar 48" dia, bears S.45½°W., 73 lks. dist. mkd. ¼ S36 BT.

Deposit the unmarked sandstone at the base of the iron post.

Fd. OK, Oct. 1984 by R. Stuntzner - M 97-80

Fd. OK, Feb. 16, 1992 by R. Ward - M 114-48

Fd. OK, Feb. 1993 by R. Ward - M 116-61