

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T20-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1874, - (DCSO records Vol. 1 Page(s) 187)

Set an Alder post 36" long, 5" dia., 18" in ground for cor. to secs. 25, 30, 31 and 36; from which
An Alder 20" dia., bears N.52°E., 75 lks. dist.
A Cedar 72" dia., bears S.60°E., 30 lks. dist.
An Alder 24" dia. bears S.85°W., 13 lks. dist.
A Hemlock 20" dia., bears N.50°W., 28 lks. dist.

Fd. and used in GLO Survey by Wm. Thiel under Contract #260 dated April 17, 1877 - (DCSO records Vol. 1 Page(s) 190)

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 200)

At the cor. of secs. 30 & 31, on the W. bdy., the post being gone, I re-establish the corner to secs. 25, 30, 31 and 36, by setting a sandstone, 12x12x4 ins., 8" in the ground marked 1 notch on S. and 5 notches on N. edges; from which
An Alder 20" dia., bears N.52°E., 75 lks. dist. mkd. T20S R9W S30 BT.
A Cedar 72" dia., bears S.60°E., 30 lks. dist. mkd. T20S R9W S31 BT.
An Alder 24" dia., bears S.85°W., 13 lks. dist. mkd. T20S R10W S36 BT.
A Hemlock 20" dia., bears N.50°W., 28 lks. dist. mkd. T20S R10W S25 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11673)

The cor. of secs. 25, 30, 31 and 36, monumented with a shattered sandstone 12x12x4 ins., firmly set 10" in the ground, with no marks remaining, beside which has been driven a galvanized iron pipe, 2" dia., 4 ft. long, 3 ft. above ground with iron cap mkd:

T
25 20 30
S
R
36 9 10 31
W

from which the remaining original bearing trees:
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T20-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Cedar 80" dia., bears S.55°E., 30 lks. dist. plainly blazed and healed. (Rec. desc., N.50°W., 28 lks. dist.)
A Hemlock 48" dia., bears N.48°W., 26 lks. dist. plainly blazed and healed. (Rec. desc. N.50°W., 28 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S
R 10 W R 9 W
S 25 S 30
S 36 S 30
1051

from which new bearing trees:

A Hemlock 48" dia., bears N.53°E., 176 lks. dist. mkd. T20S R9W S30 BT.

A Maple 40" dia., bears S.35°45'W., 94 lks. dist. mkd. T20S R10W S36 BT.

Deposit the shattered sandstone at the base of the post and reset the iron pipe alongside.

BLM resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1168, surveyed Sept/Dec. 1983 - (DCSO records Vol. 47 Page(s) 17819)

The sec. cor., perpetuated and recorded by Ronald E. Stuntzner, in 1983, determined from the remaining original bearing trees:

A Cedar 82" dia., bears S.55°E., 30 ks. dist., with healed blaze.

A Hemlock 45" dia., bears N.48°W., 26 lks. dist., with healed blaze.

and bearing trees mkd. by Tillman:

A Hemlock 55" dia., bears N.53°E., 176 lks. dist., with healed blaze.

A Maple 60" dia., bears S.33°W., 90 lks. dist., with healed blaze. (Rec. S.35 3/4°W., 94 lks.)

and a reference monument by Stuntzner:

An iron rod, 5/8" dia., firmly set, projecting 3½ ft. above ground, bears S.2°E., 9 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 2½" dia., 24" in the ground, with brass cap mkd:

T 20 S
R 10 W R 9 W
S 25 S 30
S 36 S 31
1983