

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 200)

-----  
An Alder 6" dia., which I mark  $\frac{1}{4}$  S on W. side, for  $\frac{1}{4}$  sec. cor., from which

An Alder 7" dia., bears S.54°W., 5 lks. dist. mkd.  $\frac{1}{4}$  S BT.  
A Chittem 4" dia., bears S.18°E., 18 lks. dist. mkd.  $\frac{1}{4}$  S BT

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11674)

-----  
Point for the  $\frac{1}{4}$  sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

$\frac{1}{4}$   
S 25 | S 30  
1951

from which

A Fir 10" dia., bears S.36°E., 32 lks. dist. mkd.  $\frac{1}{4}$  S30 BT  
A Fir 11" dia., bears S.31°15'W., 14 lks. dist. mkd.  $\frac{1}{4}$  S25 BT.

Survey by Les Roberts, LS #1039 - For: International Paper Co. - Oct. 8, 1982 - M 90-28

-----  
Found - 1951 GLO brass cap.  
12" Fir stump bears S.26°W., 9.3 ft., no marks.  
18" Fir bears S.36°E., 20.9 ft., scar visible.  
New BT - 28" Fir bears N.24°W., 40.8 ft., scribed.

BLM resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1168, surveyed Sept/Dec. 1983 - (DCSO records Vol. 47 Page(s) 17820)

-----  
The  $\frac{1}{4}$  sec. cor. of 25 & 30, monumented with an iron post 1" dia., firmly set, projecting 18" above ground with brass cap mkd. in 1951,

from which the remaining bearing tree mkd. by Tillman:

A Fir 16" dia., bears S.36°E., 32 lks. dist., with scribe marks  $\frac{1}{4}$  S30 bT visible on open blaze.

and a bearing tree mkd. by person(s) unknown: (See above Roberts visit)

A Fir 18" dia., bears N.24°W., 62 lks. dist., with scribe marks  $\frac{1}{4}$  S25 BT visible on open blaze.

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23082-3)

-----  
The ¼ sec. cor. of secs. 25 & 30, monumented with an iron post, 1" dia., firmly set, projecting 20" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Tillman in 1951- 52

A fir, 19" dia., bears S.36°E., 21.1 ft., with a healed blaze.

A decayed fir stump, 12" dia., bears S.26°W., 9.2 ft. no marks visible. (Record, S.31¼°W.) and the remains of a bearing tree mkd. by Les Roberts, in 1982, and reported by Robb in 1984

A roothole bears N.24°W., 40.9 ft., with a down fir, 31" dia., lying alongside, with illegible marks visible on partially healed blaze.

and a new bearing tree

A fir, 23" dia., bears N.29°W., 53.2 ft., mkd. ¼ S25 BT.